

REFERENCES

- Agrela, F., Barbudo, A., Ramirez, A., Ayuso, J., Carvajal, M. D., & Jimenez, J. R. (2012). Construction of road sections using mixed recycled aggregates treated with cement in Malaga, Spain. *Resources Conservation and Recycling*, 58, 98–106.
- Agrela, F., Sanchez, M., Ayuso, J., Geraldés, V. L., & Jimenez, J. R. (2011). Limiting properties in the characterisation of mixed recycled aggregates for use in the manufacture of concrete, *Construction and Building Materials*, 25(10), 3950–3955.
- Arandara, K. P., & Jayasinghe, C. (2008). Surface Coating for Stabilized Earth Walls. *Annual Transactions of IESL*, 1 (B), 20-30.
- Benito, M., Antoni, C., Teodoro, M., & Francisco, P. (2012). Influence of the amount of mixed recycled aggregates on the properties of concrete for non-structural use, *Construction and Building Materials*, 27(1), 612–622.
- Chen, H. J., Yen, T., & Chen, K. H. (2003). Use of building rubbles as recycled aggregates, *Cement and Concrete Research*, 33(1), 125–132.
- Dissanayake, R. M. S. (2005). *Demolition material reuse and recycling industry in Sri Lanka*. (Unpublished BSc dissertation). University of Moratuwa, Katubedda, Sri Lanka.
- Domingo, D. D. A. N. D. (2006). *Study of demolition waste management in Sri Lankan construction industry*. (Unpublished BSc dissertation). University of Moratuwa, Katubedda, Sri Lanka.
- Durisol Building Systems INC (2012). *Durisol Material*. Retrieved from <http://durisolbuild.com/material-shtml>
- Eguchi, K., Teranishi, K., Nakagome, A., Kishimoto, H., Shinozaki, K., & Narikawa, M. (2007). Application of recycled coarse aggregate by mixture to concrete construction, *Construction and Building Materials*, 21(7), 1542–1551

- Gavilan, R., & Bernold, L. (1994). *Source Evaluation of Solid waste in Building construction. Construction Engineering and mangement, 120(3), 536-552.*
- Ivana, K., Ivanka, N., & Dubravka, B. (2008). Recycled clay brick as an aggregate for concrete, *Technical Gazette, 15(3), 35-40.*
- Jayasinghe, C. (2007a). Comparative Performance of Burnt Clay Bricks and Compressed Stabilized Earth Bricks and Blocks. *ENGINEER, XXXX (02), 33-40.*
- Jayasinghe, C. (2007b). Characteristics of Different Masonry Units Manufactured with stabilized Earth. In B.V.V Reddy, & M. Mani, (eds), *International Symposium on Earthen Structures* (p.p. 252-258). India: Interline Publishing,.
- Jayasinghe, C., & Kamaladasa, N. (2007d). *Compressive strength characteristics of cement stabilized rammed earth walls. Construction and Building Materials, 21, 1971-1976.*
- Jayasinghe, C., & Mallawaarachchi, R. S. (2009a). Flexural strength of compressed stabilized earth masonry materials. *Materials and Design, 30, 3859-3868.*
- Jayasinghe, C., & Mallawaarachchi, R. S. (2009b). Quantification of Lateral Load Enhancement Potential of Masonry Walls Using Tie Beams. *Masonry International, 21 (3), 105-116.*
- Jayasinghe, C., Lakmali, H. D. D., & Rohitha, M. P. (2008). Comparative Performance of Masonry Bond Patterns. *Annual Transactions of IESL, 1 (B), 38-46.*
- Jayasinghe, C., Perera, A. A .D. A. J., & West, S. (2005). The Application of Hand Moulded Stabilized Earth Blocks for Rural Houses in Sri Lanka. In K.Heathcote (ed), *International Earth Building Conference* (pp.178-189). Sydney: Faculty of Design Architecture and Building.
- Kotler, P., & Armstrong, G. (2005). *Principles of Marketing* (10th ed.). India: Pearson.

- Loosemore, M., & Teo, M. M. M. (2001). A theory of waste behaviour in the construction industry. *Construction Management and Economics*, 19, 741-751.
- Lykidis, C., & Grigoriou, A. (2008). Hydrothermal recycling of waste and performance of the recycled wooden particleboards, *Waste Management*, 28(1), 57-63.
- Mulch Maker. (2012). *Waste-Timber-Recycling-Receiving-Station*. Retrieved from <http://www.mulchmaker.com.au>
- Osman, G., Cengiz, O., Fuat, K., Ertugrul, E., Gonzalo, M. B., & Witold, B. (2012). Properties of concrete paving blocks made with waste marble, *Journal of Cleaner Production*, 21(1), 62-70.
- Pen, C. L., Scorpio, D., & Kibert, C. (1997). Strategies for successful construction and demolition waste recycling operations. *Construction Management and Economics*, 15, 49-58.
- Perez, I., Pasandin, A. R., & Medina, L. (2012). Hot mix asphalt using C&D waste as coarse aggregates, *Materials and Design*, 36, 840-846.
- Poon, C. S., & Chan, D. (2006). Feasible use of recycled concrete aggregates and crushed clay brick as unbound road sub-base, *Construction and Building Materials*, 20(8), 578-585.
- Poon, C. S., Yu, A. T. W., & Ng, L. H. (2003). Comparison of low waste building technologies adopted in public and private housing projects in Hong Kong. *Engineering, Construction and Architectural Management*, 10, 88-98.
- Poon, C. S., Yu, A. T. W., See, C. C., & Cheung, E. (2004). Minimizing demolition waste in Hong Kong public housing projects. *Construction Management and Economics*, 22, 799-805.
- Poon, C.S., & Chan, D. (2006). Paving blocks made with recycled concrete aggregate and crushed clay bricks, *Construction and Building materials*, 20(8), 569-577.

- Poon, C.S., Kou, S.C., & Lam, L. (2002). Use of recycled aggregates in moulded concrete bricks and blocks, *Construction and Building Materials*, 16(5), 281-289.
- Poutos, K. H., Alani, A. M., Walden, P. J., & Sangha, C. M. (2008). Relative temperature changes within concrete made with recycled glass aggregate, *Construction building Materials*, 22(4), 557-565.
- Rameezdeen, R. (2009). *Construction waste management*. Colombo: COWAM.
- Richardson, A., Allain, P., & Veuille, M. (2010). Concrete with crushed, graded and washed recycled construction demolition waste as a coarse aggregate replacement, *Structural Survey*, 28(2), 142 – 148.
- Schultmann, F., & Rentz, O. (2002). Scheduling of deconstruction projects under resource constrain, *Construction Management and Economics*, 20, 391-401.
- Shantha, K. S. (2008). *Identification of potential for recycling of demolition waste in Sri Lanka*. (Unpublished BSc dissertation). University of Moratuwa, Katubedda, Sri Lanka.
- Subashi, G. H. M. J., Wasantha, P. L. P., Jayasuriya, J. P. B., & Kandage, J.D. (2010). Properties of masonry blocks manufactured with crushed demolition waste. In *Proceeding of the Seventh Academic Sessions, University of Ruhuna Galle*, (pp.1-11).
- Treloar, G. J., Guptha, H., Peter, E. D. L., & Nguyen, B. (2003). An analysis of factors influencing waste minimization and use of recycled materials for the construction of residential buildings. *Management of Environmental Quality: An International Journal*. 14, 134-145.
- Vetrazzo. (2011). *Recycled glass surfaces portfolio*. Retrieved from <http://www.vetrazzo.com/eng/realisations/index>
- Xiao, Z., Ling, T. C., Kou, S. C., Wang, Q., & Poon, C. S. (2011). Use of wastes derived from earthquakes for the production of concrete masonry partition wall blocks, *Waste Management*, 31(8), 1859-1866.
- Yeung, A. T., Tham, L. G., Lee, P. K. K., Mok, K. Y., & Pei, G. (2007). Use of inert C & D materials for seawall foundation: Quality control measures, *Waste Management*, 27(6), 768-777.