

**FEASIBILITY OF A COGENERATION SYSTEM IN A
MEDIUM SIZE HOTEL IN SRI LANKA**

MOHAMED RIYAAZ

(08/10423)

Master of Science

Department of Mechanical Engineering

University of Moratuwa

Sri Lanka

March 2012

**FEASIBILITY OF A COGENERATION SYSTEM IN A
MEDIUM SIZE HOTEL IN SRI LANKA**

MOHAMED HANIFA MOHAMED RIYAAZ

(08/10423)

Dissertation submitted in partial fulfillment of the requirements for the degree of
Master of Science in Building Services Engineering

Department of Mechanical Engineering

University of Moratuwa

Sri Lanka

March 2012

DECLARATION

“I declare that this is my own work and this dissertation does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any other University or institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text”.

Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my dissertation, in whole or in part in print, electronic or other medium. I retain the right to use this content in whole or part in future works (such as articles or books).

Signature:

MHM Riyaz

Date:

The above candidate has carried out research for the Masters Dissertation under my supervision.

Signature of the supervisor:

Prof. R.A. Attalage

Date:

ACKNOWLEDGEMENT

Through the MSc/PG Dip in Building Services Engineering course, I am benefited to do a Research Project on “Feasibility of a cogeneration system in a medium size hotel in Sri Lanka”. Comprehensive support, guidance and encouragement were the main driving forces, which contributed to the completion of the task within the expected time. I sincerely thank Professor R. A. Attalage, Professor of Mechanical Engineering, University of Moratuwa and course coordinator Master of Science, programmed 2008/2009 and Mechanical Engineering Department, University of Moratuwa for their commitment, supervision and coordination.

I again give my sincere thanks to Professor R. A. Attalage, Professor of Mechanical Engineering, University of Moratuwa, for his help and encouragement during the Research Project.

A word of thanks is due to Mr. Nalin Wijekoon Managing Director and Mr.Somarathna Director (M & E), of Design Consortium Limited for providing me support to collect the technical details of Hotels. I again give my thanks to Mr. Rohitha Rajaratne vice president and Mr.Chula Attapattu Deputy General Manager, of Aitken Spence Hotels for their genuine corporation in collecting valuable information and the approval to implement this project to the one of the Aitken Spence Hotels in Sri Lanka.

I would like to thank all the academic staff and non academic staffs who were engaged in the Master of Science in Building Services Engineering program me 2008/2009, University of Moratuwa.

Finally, I would like to express my appreciation to my mother, my brothers and my wife for their continued patience, understanding and support throughout the preparation of this report.

MHM Riyaz

ABSTRACT

By cogeneration, electricity and thermal energy can be produced by one prime energy source simultaneously. Using cogeneration systems to provide electricity, hot water and chilled water for hotels and hospital buildings seems to be a perfectly logical solution. The principle of cogeneration systems is simple and the technology is both well known and reliable. It helps to reduce energy costs, better fuel utilization, improve plant energy efficiency, reduce electricity consumption due to absorption chilling and as a whole reduce greenhouse gas emission.

In Sri Lanka, huge quantity of money is expended to import petroleum fuels for transportation, industrial, etc., and power generation purposes. Last year in Sri Lanka thermal power generation was recorded more than 60% of total power generations. However in thermal power generation, efficiency is normally less than 35%. Since cogeneration systems could produce electricity, hot water & chilled water, the overall efficiency could be more than 80%.

To implement a cogeneration system in three star class hotels in this study, information and data was collected from several hotels in relation to the monthly total power consumption, annual occupancy and number of guest rooms. All of these hotels operate alike and are similar to the three star class hotel operations. Based on the collected data and information three different scenarios for the proper analysis have been considered.

As a result of this cogeneration system, hotel saves 2,078 kWh electricity units per day and capital cost increased 25.7 million rupees, which can be recovered in less than the three years' time. Further to that annually it saves 10 to 11 million rupees from the operational and maintenance costs when considering the scenario 2.

In Sri Lanka 15% losses indicate for electricity transmission and distribution system. Subsequent to that, because of this system it is expected to saves 2,445 kWh per day and more than 800,000 kWh per year in this project. When considering the environmental aspect reduction of 400 tons per year of CO₂ to the atmosphere.

TABLE OF CONTENT

Declaration of the candidate & Supervisor	i
Acknowledgements	ii
Abstract	iii
Table of content	iv
List of Figures	viii
List of Tables	x
1. Introduction	1
1.1 Background of Research	1
1.2 Benefits from the cogeneration system	6
1.3 Objective of the research project and Methodology	7
1.4 Assumptions, input data, limitation and constrains	7
2. Theoretical Framework of Cogeneration System and Diesel Engine	8
2.1 Cogeneration system	8
2.2 Technical Options for Cogeneration	9
2.2.1 Steam Turbine Cogeneration System	9
2.2.2 Gas Turbine Cogeneration System	10
2.2.3 Reciprocating Engine Cogeneration System	11
2.3 Other Classifications of Cogeneration Systems	12
2.3.1 Topping Cycle	13
2.3.2 Bottoming Cycle	13
2.4 Important Technical Parameters for Cogeneration	13
2.4.1 Heat to Power Ratio	13
2.4.2 Quality of Thermal Energy Needed	14
2.4.3 Load Pattern	14
2.4.4 Fuels Available	15
2.5 Prime movers & Electric Generators	16
2.5.1 Reciprocating Internal Combustion (IC) Engine	
Base Cogeneration system	17
2.5.2 Principle of Operation	17

2.5.3	Performance Characteristics	19
2.5.4	Technology Overview	24
2.5.5	Advantages and Disadvantages	26
2.6	Summary and Conclusion	27
3.	Theoretical concepts of vapour absorption chillers & exhaust gas	28
3.1	Absorption Chillers	28
3.2	Refrigerant-Absorbent Selection	31
3.2.1	Water Lithium Bromide vapour absorption system	32
3.3	Properties of water-lithium bromide solutions	32
3.3.1	Composition	32
3.3.2	Vapour Pressure of Water-Lithium Bromide Solution	33
3.3.3	Enthalpy of Water-Lithium Bromide Solution	36
3.3.4	Enthalpy Values for Pure Water	37
3.3.5	Crystallization	37
3.4	Commercial systems	38
3.5	Heat sources for water-lithium bromide systems	42
3.5.1	Minimum Heat Source Temperatures for Li-Br Water system	42
3.6	Capacity control	43
3.7	Application	44
3.8	Practical problems in water-lithium bromide systems	55
3.9	Disadvantages of Absorption Chillers	56
3.10	Summary and Conclusion	56
4.	Establishments of Assumptions	57
4.1	Introduction	57
4.2	Information and Analysis	57
4.3	Hotel “A” Data Analysis	58
4.3.1	Hotel “A” Data	58
4.3.2	Hotel “A” Data Analysis	59
4.4	Hotel “B” Data Analysis	60

4.4.1	Hotel “B” Data	61
4.4.2	Hotel “B” Data Analysis	61
4.5	Hotel “C” Data Analysis	63
4.5.1	Hotel “C” Data	63
4.5.2	Hotel “C” Data Analysis	64
4.6	Hotel “D” Data Analysis	66
4.6.1	Hotel “D” Data	66
4.6.2	Hotel “D” Data Analysis	67
4.7	Summary and Conclusion	68
5.	Design a Cogeneration System	70
5.1	Information & Data	70
5.2	Calculation of Electricity Requirements	71
5.2.1	Proposed Building Electrical Consumption Requirements	71
5.2.2	Existing Building Electrical Consumption Requirements	73
5.3	Heat to power ratio	75
5.4	Generator Supply air & Exhaust Gas Conditions	76
5.4.1	Theoretical & Actual Air Calculation	76
5.4.2	Exhaust Gas Flow Rate Calculation	78
5.4.3	Exhaust gas Chiller Capacity Calculation	79
5.4.4	Heat Recovery from Engine Jacket Water	79
5.5	Data Analysis	80
5.6	Scenario 1	83
5.6.1	Operational Cost Calculation	83
5.6.2	Maintenance Cost Calculation	86
5.6.3	Capital Cost Calculation	88
5.7	Scenario 2	88
5.7.1	Operational Cost Calculation	88
5.7.2	Maintenance Cost Calculation	93
5.7.3	Capital Cost Calculation	95

5.8	Scenario 3	95
5.8.1	Operational Cost Calculation	95
5.8.2	Maintenance Cost Calculation	101
5.8.3	Capital Cost Calculation	102
5.9	Scenario -1 Vs Scenario – 2	103
5.10	Scenario -1 Vs Scenario – 3	104
6.	Discussion and conclusion	106
	Reference List	111

LIST OF FIGURES

	Page	
Figure 1.1	Efficiency of Central Power Generation	3
Figure 1.2	Efficiency of Combined-Cycle Power Generation	4
Figure 1.3	Efficiency of CHP System	5
Figure 2.1	Schematic diagrams of steam turbine cogeneration systems	9
Figure 2.2	Schematic diagram for gas cogeneration system	11
Figure 2.3	Schematic diagram of reciprocating engine cogeneration	12
Figure 2.4	Different heat and power demand patterns in two factories	15
Figure 2.5	Heat balance of reciprocating internal combustion engine	20
Figure 2.6	Otto and Diesel Cycle Thermal Efficiencies as Functions of Compression Ratio	26
Figure 3.1	Vapor-Compression Cycles Schematic	29
Figure 3.2	Basic Absorption Cycle Schematic	30
Figure 3.3	A Typical Duhring Plot	34
Figure 3.4	H ₂ O- LiBr System with a solution heat exchanger on Duhring Plot	35
Figure 3.5	Pressure-Temperature-Concentration diagram for H ₂ O-LiBr solution	35
Figure 3.6	Enthalpy –Temperature - Concentration diagram for H ₂ O-LiBr solution	36
Figure 3.7	A commercial, twin-drum type, water-lithium bromide system	38
Figure 3.8	A commercial, single-drum type, water-lithium bromide system	39
Figure 3.9	Double-Effect Water/Lithium Bromide Absorption Chillers Schematic	40
Figure 3.10	A commercial, double-effect, water-lithium bromide system	41
Figure 3.11	Double effect VARS on Dühring plot	42
Figure 3.12	Schematic diagram for typical exhaust fired absorption chiller	45
Figure 3.13	Schematic diagrams for cogeneration system with absorption chiller	46
Figure 5.1	Both building total power demand Vs time	74

Figure 5.2	Power combination (CEB & Generator)-Scenario 2	81
Figure 5.3	Power combination (CEB & Generator)-Scenario 2	89
Figure 5.4	Power combination (CEB & Generator)-Scenario 3	82
Figure 5.5	Power combination (CEB & Generator)-Scenario 3	96
Figure 5.6	Recovery period of both Scenario2 & 3 Vs Scenario 1	105

LIST OF TABLES

		Page
Table 1.1	Sri Lanka Thermal Power Generation Sources in 2010	2
Table 2.1	Heat-to-power ratios and other parameters of cogeneration systems	12
Table 2.2	Reciprocating engines speed classifications	15
Table 2.3	Internal combustion engine co-generation process	18
Table 2.4	Representative NOx Emissions from Reciprocating Engines	20
Table 3.1	Application data for a single-stage water-lithium bromide system	38
Table 4.1	Monthly power consumption of Hotel “A”	45
Table 4.2	Annual occupancy range of Hotel “A”	45
Table 4.3	Power consumption details per room per day of Hotel “A”	46
Table 4.4	Monthly power consumption of the Hotel “B”	47
Table 4.5	Annual occupancy range of the Hotel “B”	48
Table 4.6	Power consumption details per room per day of the Hotel “B”	48
Table 4.7	Monthly power consumption of the Hotel “C”	50
Table 4.8	Annual occupancy range of the Hotel “C”	50
Table 4.9	Power consumption details per room per day of the Hotel “C”	50
Table 4.10	Monthly power consumption of the Hotel “D”	52
Table 4.11	Annual occupancy range of the Hotel “D”	52
Table 4.12	Power consumption details per room per day of the Hotel “D”	53
Table 5.1	Summary of the both building total power demand	58
Table 5.2	Propose building monthly CEB charges (Scenario 1)	66
Table 5.3	Existing building monthly CEB charges (Scenario 1)	66
Table 5.4	Total fuel charges (Scenario 1)	68
Table 5.5	Maintenance costs for the scenario 1	69
Table 5.6	Total operation & maintenance cost for scenario 1	69
Table 5.7	Total capital cost for scenario 1	70
Table 5.8	Both building total power demand and combinations of the CEB / Generators (scenario 2)	70
Table 5.9	Propose building total cooling load combinations of the chillers (Scenario 2)	71

Table 5.10	Existing building total cooling load combinations of the chillers (Scenario 2)	71
Table 5.11	Propose building power consumption increase due to the cooling Load sharing with the screw chiller (Scenario 2)	72
Table 5.12	Existing building power consumption increase/ decrease due to the cooling load sharing with the absorption chiller (Scenario 2)	72
Table 5.13	Propose building monthly CEB charges (Scenario 2)	72
Table 5.14	Existing building monthly CEB charges (Scenario 2)	73
Table 5.15	Total fuel charges (Scenario 2)	74
Table 5.16	Total Maintenance cost (Scenario 2)	75
Table 5.17	Total Operational & Maintenance cost (Scenario 2)	75
Table 5.18	Total capital cost (Scenario 2)	76
Table 5.19	Both building total power demand and combinations of the CEB / Generators (Scenario 3)	76
Table 5.20	Propose building total cooling load combinations of the chillers (Scenario 3)	77
Table 5.21	Existing building total cooling load combinations of the chillers (Scenario 3)	77
Table 5.22	Propose building power consumption increase due to the cooling load sharing with the screw chiller (Scenario 3)	78
Table 5.23	Existing building power consumption increase/ decrease due to the cooling load sharing with the absorption chiller (Scenario 3)	78
Table 5.24	Propose building monthly CEB charges (Scenario 3)	78
Table 5.25	Existing building monthly CEB charges (Scenario 3)	79
Table 5.27	Total Maintenance cost (Scenario 3)	81
Table 5.28	Total Operational & Maintenance cost (Scenario 3)	81
Table 5.31	Scenario 1 Vs Scenario 2	82
Table 5.32	Scenario1 Vs Scenario 3	83