

REFERENCES

- [1] Anthony D. Matthews, Thomas C. Montgomery, Daniel A. Cook, John W. Oeschger, and John S. Stroud "12.75" Synthetic Aperture Sonar (SAS), High Resolution and Automatic Target Recognition", MTS/IEEE Oceans 2006 Boston, 2006, pp.1001-1007.
- [2] Chun-Chieh Hsiao,Polly Huang," Two Practical Considerations of Beacon Deployment for Ultrasound-Based Indoor Localization Systems",IEEE International Conference on Sensor Networks, Ubiquitous, and Trustworthy Computing, 2008, pp. 306-311.
- [3] Junhui Zhao, Yongcai Wang NEC Labs and Beijing " Autonomous Ultrasonic Indoor Tracking System" ,International Symposium on Parallel and Distributed Processing with Applications, 2008,pp.532-539.
- [4] Kazunori UMEDA,Jun OTA, Hisayuki KIMURA,"Fusion of multiple ultrasonic sensor data and imagery data for measuring moving obstacle's motion",IEEE/SICE/RSJ International Conference on Multisensor Fusion and Integration for Intelligent Systems,1999,pp742-748.
- [5] Ricardo Gutierrez-Osuna, Jason A. Janetand Ren C. Luo " Modeling of Ultrasonic Range Sensorsfor Localization of AutonomousMobile Robots", IEEE Transactions on Industrial Electronics,Vol. 45, No. 4, August 1998,pp,654-662.
- [6] Jarosław Majchrzak, Mateusz Michalski, and Grzegorz Wiczyn'ski " Distance Estimation With a Long-Range Ultrasonic Sensor System", IEEE Sensors Journal,Vol. 9, No. 7, July 2009, pp.767-773.
- [7] Armin Runge, Marcel Baunach and Reiner Kolla "Precise Self-Calibration of Ultrasound Based Indoor Localization Systems", International Conference On Indoor Positioning And Indoor Navigation (IPIN), 21-23 September 2011,pp 1-8.