TRAJECTORY PLANNING FOR 6-DOF ROBOT MANIPULATOR BASED ON OFFLINE ROBOT PROGRAMMING APPROACH

Malnydelage Dimithri Maliyos Fernando

(148456D)

Degree of Master of Science

Department of Electronic and Telecommunication Engineering

University of Moratuwa

Sri Lanka

January 2019

TRAJECTORY PLANNING FOR 6-DOF ROBOT MANIPULATOR BASED ON OFFLINE ROBOT PROGRAMMING APPROACH

Malnydelage Dimithri Maliyos Fernando

(148456D)

Thesis submitted in partial fulfillment of the requirements for the degree Master of Science in Electronics and Automation

Department of Electronic and Telecommunication Engineering

University of Moratuwa

Sri Lanka

January 2019

DECLARATION, COPYRIGHT STATEMENT AND THE STATEMENT OF THE SUPERVISOR

"I declare that this is my own work and this thesis does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any other University or institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text".

"Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my thesis, in whole or in part in print, electronic or other medium. I retain the right to use this content in whole or part in future works (such as articles or books)".

Signature:	Date:
The above candidate has carried out research for the Master supervision.	's Thesis under my
Name of the supervisor: Prof. Rohan Munasinghe	
Signature of the supervisor:	Date:

ABTRACT

Industrial robot manipulators are highly involved in modern manufacturing industries. Robot programming is the procedure to carry out generating a sequence of robot instruction. Teaching method is highly applied where a teach pendent is used to generate the robot programme by teaching one point at a time. This process tends to consume more time and the accuracy can be varied depends on the application. Several other methods are used to program robot movement nevertheless industrial applications of these systems are still developing. Programming tends to be difficult and restricts the productivity and industrial application. Hence, requirement of flexible programming methods is still challenging for inexpert robot operators. Trajectory planning for a robot system is still a developing area where the accuracy, productivity and high quality on various operations are highly concerned. To address these limitations, off-line programming systems can be used where computer systems with realistic graphics, interfaces and features can be used to plan and program robot motions without using robot hardware. The research is aimed to present methods for finding a better mathematical way of optimized trajectory planning of 6-DOF industrial robot manipulator. Computer Aided Design software systems are used to implement off-line programming technique by developing human robot interface in order to create robot moving sequence and achieve required data for further calculations. Welding process of machine head cover using a 6 DOF robot manipulator is used to demonstrate and evaluate the proposed method. Methods for Point allocation along the robot moving path and data extraction are presented. Inverse kinematic model for the 6 DOF manipulator is developed and implemented in order to get joint space data represented by joint angles. Derived data is studied to analyze the manipulator motion behavior while moving along predefined path via points allocated. Robot path planning and trajectory planning with CAD system involvement as off-line programming technique is analyzed by comparing results in order to evaluate the performance of the proposed method.

Keywords: Offline robot programming, Computer Aided Design, 6 DOF robot manipulator, inverse kinematics, Human robot interface

ACKNOWLEDGEMENT

The basis of this master thesis is originated by an industrial project which was planned and implemented in MAS Holdings Pvt Limited. I would like to express my sincere gratitude to Mr. Randy Rajarathnam; General Manager- Technical, Mr. Maduranga Pemarathne; Manager-Innovation as the project managers and for giving me technical support to succeed this project. Further, I am sincerely grateful to other members of project team for their support throughout the project and the research.

I am profoundly grateful to my supervisor, Prof. Rohan Munasinghe who has motivated me with intense guidance and great supervision throughout the research. I am also grateful to course coordinator of the MSc programme in Electronics and Automation; Dr. Chamira Edussooriya for the guidance and advises given throughout the research. I am thankful to Mr. Damith Kandage; course assistant for providing assistances given throughout the whole duration of the research and finally I would like to thank all the academic staff members and supportive staff members who supported and inspired me by supporting whenever needed throughout the research.

Malnydelage Dimithri Maliyos Fernando B.Sc. Eng. (Moratuwa) Department of Mechanical Engineering, University of Moratuwa, Katubedda, Sri Lanka, January 2019.

TABLE OF CONTENTS

DECLARATION, COPYRIGHT STATEMENT AND THE STATEME	
ABTRACT	ii
ACKNOWLEDGEMENT	iii
LIST OF FIGURES	vi
LIST OF TABLES	viii
LIST OF ABBREVIATIONS	viii
LIST OF APPENDICES	ix
INTRODUCTION	1
1.1 Background and Motivation	1
1.2. Problem Definition	5
1.2.1 Thesis Objectives	6
1.2.2 Goals	6
1.3 Limitations	6
1.4 Influences to the industry	7
1.5. Report Summary	7
LITERATURE REVIEW	9
2.1 Some Literature	9
ROBOT AND APPLICATION SYSTEM	13
3.1 Robot system	13
3.2 Automated welding operation	18
3.3 Robotic welding Robot cell	20
SYSTEM AND PROCESS DESIGN IDENTIFICATION	24
4.1 Mathematical approach for closed form solution of inverse robot manipulator	
4.1.1 Robot manipulator forward kinematics	26
4.1.2 Robot manipulator inverse kinematics	28
4.2 The Human Robot interface	33
4.3 Path planning and information extraction	38
4.4 Mathematical approach for mapping trajectories	40
SYSTEM DESIGN AND SIMULATION	47
5.1 Design and Implementation of Inverse kinematic model	47