

8 References

- Ali, K. (2017). *Advances and Challenges in Flash Flood Risk Assessment: A Review*.
<https://doi.org/10.4172/2167-0587.1000195>
- Amiri, B. J., Fohrer, N., Cullmann, J., Hörmann, G., Müller, F., & Adamowski, J. (2016). Regionalization of Tank Model Using Landscape Metrics of Catchments. *Water Resources Management*, 30(14), 5065–5085.
<https://doi.org/10.1007/s11269-016-1469-5>
- Arifjaya, N. M., Kusmana, C., Abdullah, K., & Prasetyo, L. B. (2011). Application of Tank Model for Predicting Water Balance and Flow Discharge Components of Cisadane Upper Catchment. *Jurnal Manajemen Hutan Tropika*, 17(2), 63–70.
<https://doi.org/10.7226/jmht.17.2.63-70>
- Bai, Y., Wagener, T., & Reed, P. (2009). A top-down framework for watershed model evaluation and selection under uncertainty. *Environmental Modelling and Software*, 24(8), 901–916. <https://doi.org/10.1016/j.envsoft.2008.12.012>
- Basri, H. (2013). Development of Rainfall-runoff Model Using Tank Model: Problems and Challenges in Province of Aceh, Indonesia. *Aceh International Journal of Science and Technology*, 2(1), 26–36.
- Beven, K. (2012). *Rainfall-Runoff Modelling* (2nd ed.). John Wiley & Sons, Ltd Wiley-Blackwell. <https://doi.org/10.1002/9781119951001>
- Beven, K. J. (2012). *Rainfall-Runoff Modelling: The Primer* (2 edition). Wiley-Blackwell. <https://books.google.lk/books?id=eI-jjITirlAC&printsec=frontcover#v=onepage&q&f=false>
- Bourdin, D. R., Fleming, S. W., & Stull, R. B. (2012). Streamflow Modelling: A Primer on Applications, Approaches and Challenges. *Atmosphere-Ocean*, 50(4), 507–536. <https://doi.org/10.1080/07055900.2012.734276>
- Broderick, C., Matthews, T., Wilby, R. L., Bastola, S., & Murphy, C. (2016). Transferability of hydrological models and ensemble averaging methods between contrasting climatic periods. *Water Resources Research*, 52(10), 8343–8373.
<https://doi.org/10.1002/2016WR018850>

- Cao Don, N., Araki, H., Yamanishi, H., & Koga, K. (2005). Development and Application of a Rainfall-runoff Model:-A Proposal of Storage Channel Concept. *JOURNAL OF JAPAN SOCIETY OF HYDROLOGY & WATER RESOURCES*, 18(3), 257–273. <https://doi.org/10.3178/jjshwr.18.257>
- Chow, V. Te, Maidement, D. R., & Mays, L. W. (1988). *Applied hydrology*. McGraw-Hill, Inc.
- Devaliya, S., Tiwari, H. L., & Balvanshi, A. (2017). Runoff Estimation of a Basin Using Tank Model. *International Journal of Emerging Research in Management and Technology*, 6(5), 51–53. <https://doi.org/10.23956/ijermt/sv6n4/128>
- Devia, G. K., Ganasri, B. P., & Dwarakish, G. S. (2015). A Review on Hydrological Models. *Aquatic Procedia*, 4(Icwrcoe), 1001–1007. <https://doi.org/10.1016/j.aqpro.2015.02.126>
- Dissanayake, P. K. M. (2017). *Applicability of a two-parameter water balance model to simulate daily rainfall runoff – case study of Kalu and Gin river basins in Sri Lanka*. Unpubl. MSc Thesis. University of Moratuwa.
- Excel Solver: Which Solving Method Should I Choose? | EngineerExcel*. (n.d.). Retrieved September 1, 2020, from <https://engineerexcel.com/excel-solver-solving-method-choose/>
- Flood-Runoff Analysis*. (1994). US Army Corps of Engineers. https://www.publications.usace.army.mil/portals/76/publications/engineermanuals/em_1110-2-1417.pdf
- Fowler, K., Peel, M., Western, A., & Zhang, L. (2018). Improved Rainfall-Runoff Calibration for Drying Climate: Choice of Objective Function. *Water Resources Research*, 54(5), 3392–3408. <https://doi.org/10.1029/2017WR022466>
- Gan, T. Y., Dlamini, E. M., & Biftu, G. F. (1997). Effects of model complexity and structure, data quality, and objective functions on hydrologic modeling. *Journal of Hydrology*, 192(1–4), 81–103. [https://doi.org/10.1016/S0022-1694\(96\)03114-9](https://doi.org/10.1016/S0022-1694(96)03114-9)
- Garcia, F., Folton, N., & Oudin, L. (2017). Which objective function to calibrate

- rainfall–runoff models for low-flow index simulations? *Hydrological Sciences Journal*, 62(7), 1149–1166. <https://doi.org/10.1080/02626667.2017.1308511>
- Goswami, M., O'Connor, K. M., & Bhattarai, K. P. (2007). Development of regionalisation procedures using a multi-model approach for flow simulation in an ungauged catchment. *Journal of Hydrology*, 333(2–4), 517–531. <https://doi.org/10.1016/j.jhydrol.2006.09.018>
- Green, I. R. A., & Stephenson, D. (2009). *Criteria for comparison of single event models*. 6667(1986). <https://doi.org/10.1080/02626668609491056>
- Hansen, D. P., Ye, W., Jakeman, A. J., Cooke, R., & Sharma, P. (1996). Analysis of the effect of rainfall and streamflow data quality and catchment dynamics on streamflow prediction using the rainfall-runoff model IHACRES. *Environmental Software*, 11(1–3), 193–202. [https://doi.org/10.1016/S0266-9838\(96\)00048-2](https://doi.org/10.1016/S0266-9838(96)00048-2)
- Kamran, M., & Rajapakse, R. L. H. L. (2018). Effect of Watershed Subdivision and Antecedent Moisture Condition on HEC-HMS Model Performance in the Maha Oya Basin, Sri Lanka. *International Journal of Engineering Technology and Sciences*, 5(2), 22–37. <https://doi.org/10.15282/ijets.5.2.2018.1004>
- Kavetski, D., Fenicia, F., & Clark, M. P. (2011). Impact of temporal data resolution on parameter inference and model identification in conceptual hydrological modeling: Insights from an experimental catchment. *Water Resources Research*, 47(5). <https://doi.org/10.1029/2010WR009525>
- Kim, K. B., Kwon, H. H., & Han, D. (2018). Exploration of warm-up period in conceptual hydrological modelling. *Journal of Hydrology*, 556(November), 194–210. <https://doi.org/10.1016/j.jhydrol.2017.11.015>
- Kuok, K. K., Harun, S., & Chiu, P. (2011). Investigation Best Number of Tanks for Hydrological Tank Model for Rural Catchment in Humid Region. *The Institution of Engineers, Malaysia*, 72(4), 1–11. [D--internet-myiemorgmy-iemms-assets-doc-alldoc-document-1591_Journal_Dec2011_Complete \(1\).pdf](D:\internet-myiemorgmy-iemms-assets-doc-alldoc-document-1591_Journal_Dec2011_Complete (1).pdf)
- Kuok, K. K., Harun, S., & Shamsuddin, S. M. (2010). Global Optimization Methods

- for Calibration and Optimization of the Hydrologic Tank Model ' s Parameters. *Canadian Journal on Civil Engineering*, 1(1), 1–14.
- LEE, G., TACHIKAWA, Y., SAYAMA, T., & TAKARA, K. (2008). Internal Response of Catchment To Plausible Parameter Sets Under Equifinality. *Proceedings of Hydraulic Engineering*, 52, 79–84. <https://doi.org/10.2208/prohe.52.79>
- Li, C. Z., Wang, H., Liu, J., Yan, D. H., Yu, F. L., & Zhang, L. (2010). Effect of calibration data series length on performance and optimal parameters of hydrological model. *Water Science and Engineering*, 3(4), 378–393. <https://doi.org/10.3882/j.issn.1674-2370.2010.04.002>
- Lu, L., Jun, X., Xu, C. Y., Jianjing, C., & Rut, W. (2009). Analyse the sources of equifinality in hydrological model using GLUE methodology. *IAHS-AISH Publication*, 331(September), 130–138.
- Marshall, L., Nott, D., & Sharma, A. (2005). Hydrological model selection: A Bayesian alternative. *Water Resources Research*, 41(10). <https://doi.org/10.1029/2004WR003719>
- Mcdonnell, R. A. (2008). Challenges for Integrated Water Resources Management: How Do We Provide the Knowledge to Support Truly Integrated Thinking? *International Journal of Water Resources Development*, 24(1), 131–143. <https://doi.org/10.1080/07900620701723240>
- Merz, R., & Blöschl, G. (2004). Regionalisation of catchment model parameters. *Journal of Hydrology*, 287(1–4), 95–123. <https://doi.org/10.1016/j.jhydrol.2003.09.028>
- Meteorological Department. (n.d.). *Weather and Climate Data*. Retrieved August 31, 2020, from http://www.meteo.gov.lk/index.php?option=com_content&view=article&id=100&Itemid=321&lang=en#page1
- Musiake, K., & Wijesekera, N. T. S. (1990). Streamflow Modelling of Sri Lankan Catchment Considering Spatial Variation of Rainfall.pdf. *Japan Society of*

Hydrology and Water Resources, August 1990, 575–576.

- Norliyana Wan Ismail, W., Zawiah Wan Zin, W., & Ibrahim, W. (2017). Estimation of rainfall and stream flow missing data for Terengganu, Malaysia by using interpolation technique methods. In *Journal of Fundamental and Applied Sciences* (Vol. 13, Issue 3). <https://mjfas.utm.my/index.php/mjfas/article/view/578>
- Orellana, B., Pechlivanidis, I. G., McIntyre, N., Wheater, H. S., & Wagener, T. (2008). *A toolbox for the identification of parsimonious Semi-Distributed Rainfall-Runoff models: Application to the Upper Lee catchment. 1*(January), 670–677.
- Ou, X., Gharabaghi, B., McBean, E., & Doherty, C. (2017). Investigation of the Tank Model for Urban Storm Water Management. *Journal of Water Management Modeling*, 1–5. <https://doi.org/10.14796/jwmm.c421>
- Paik, K., Kim, J. H., Kim, H. S., & Lee, D. R. (2005). A conceptual rainfall-runoff model considering seasonal variation. *Hydrological Processes*, 19(19), 3837–3850. <https://doi.org/10.1002/hyp.5984>
- Patil, S. D., & Stieglitz, M. (2015). Comparing spatial and temporal transferability of hydrological model parameters. *JOURNAL OF HYDROLOGY*, 525, 409–417. <https://doi.org/10.1016/j.jhydrol.2015.04.003>
- Pechlivanidis, I. G., Jackson, B. M., McIntyre, N. R., & Wheater, H. S. (2011). Catchment scale hydrological modelling: A review of model types, calibration approaches and uncertainty analysis methods in the context of recent developments in technology and applications. *Global Nest Journal*, 13(3), 193–214. <https://doi.org/10.30955/gnj.000778>
- Perrin, C., Michel, C., & Andréassian, V. (2001). Does a large number of parameters enhance model performance? Comparative assessment of common catchment model structures on 429 catchments. *Journal of Hydrology*, 242(3–4), 275–301. [https://doi.org/10.1016/S0022-1694\(00\)00393-0](https://doi.org/10.1016/S0022-1694(00)00393-0)
- Phien, H. N., & Pradhan, P. S. S. (1983). the Tank Model in Rainfall-Runoff Modelling. *Water SA*, 9(3), 93–102.

- Plate, E. J. (1993). Sustainable Development of Water Resources: A Challenge to Science and Engineering. *Water International*, 18(2), 84–94. <https://doi.org/10.1080/02508069308686154>
- Ponrajah, A. J. P. (1984). *Design of Irrigation Headworkds for Small Catchments*. Irrigation Department.
- Premalal, R., Silva, D., & Dayawansa, N. D. K. (2007). A comparison of methods used in estimating missing rainfall data Climate change, water and food security assessment in Deduru Oya basin View project Biomass estimation of vegetation types View project. *Article in Journal of Agricultural Sciences*. <https://doi.org/10.4038/jas.v3i2.8107>
- Ramasastri, K. S. (1990). Simulation of daily runoff in a mountainous catchment using the tank model. *Hydrology in Mountainous Regions I*, 193, 623–626.
- Razavi, T., Coulibaly, P., & Asce, M. (2012). Streamflow Prediction in Ungauged Basins: Review of Regionalization Methods. *Journal of Hydrologic Engineering*, 18(8), 958–975. [https://doi.org/10.1061/\(ASCE\)HE.1943-5584.0000690](https://doi.org/10.1061/(ASCE)HE.1943-5584.0000690)
- Samuel, J., Coulibaly, P., & Metcalfe, R. A. (2011). Estimation of continuous streamflow in ontario ungauged basins: Comparison of regionalization methods. *Journal of Hydrologic Engineering*, 16(5), 447–459. [https://doi.org/10.1061/\(ASCE\)HE.1943-5584.0000338](https://doi.org/10.1061/(ASCE)HE.1943-5584.0000338)
- Setiawan, B. I., Fukuda, T., & Nakano, Y. (2003). Developing Procedures for Optimization of Tank Model's Parameters. *Agricultural Engineering International: The CIGR Journal of Scientific Research and Development*, 13.
- Shu, C., & Ouarda, T. B. M. J. (2012). Improved methods for daily streamflow estimates at ungauged sites. *Water Resources Research*, 48(2), 1–15. <https://doi.org/10.1029/2011WR011501>
- Singh, V. P., & Frevert, D. K. (Eds.). (2001). *Mathematical Models of Large Watershed Hydrology*. Water Resources Pubns. <https://books.google.lk/books?id=abRyo4OLjgYC&printsec=frontcover#v=onepage&q&f=false>

- Singh, V. P., & Woolhiser, D. A. (2003). Mathematical Modeling of Watershed Hydrology. *Perspectives in Civil Engineering: Commemorating the 150th Anniversary of the American Society of Civil Engineers*, 345–367.
- Sitterson, J., Knightes, C., Parmar, R., Wolfe, K., Muche, M., & Avant, B. (2017). *An Overview of Rainfall-Runoff Model Types*.
- Sivapalan, M., Takeuchi, K., Franks, S. W., Gupta, V. K., Karambiri, H., Lakshmi, V., Liang, X., McDONNELL, J. J., Mendiondo, E. M., O’Connell, P. E., Oki, T., Pomeroy, J. W., Schertzer, D., Uhlenbrook, S., & Zehe, E. (2003). IAHS Decade on Predictions in Ungauged Basins (PUB), 2003–2012: Shaping an exciting future for the hydrological sciences. *Hydrological Sciences Journal*, 48(6), 857–880. <https://doi.org/10.1623/hysj.48.6.857.51421>
- Song, J. H., Her, Y., Park, J., Lee, K. Do, & Kang, M. S. (2017). Simulink Implementation of a Hydrologic Model: A Tank Model Case Study. *Water (Switzerland)*, 9(9), 1–17. <https://doi.org/10.3390/w9090639>
- Sugawara, M. (1957). On the Analysis of Runoff Structure About Several Japanese Rivers. *Research memoir of the Ins. of statistical math*: 1-76.
- Sugawara, M. (1967). The Flood Forecasting by a Series Storage Type Model. *Int.Symposium Floods and their Computation*, International Association of HydrologicSciences,1–6.
- Sugawara, M. (1979). Automatic calibration of the tank model. *Hydrological Sciences Bulletin*, 24(3), 375–388. <https://doi.org/10.1080/02626667909491876>
- Sugawara, M. (1984). Tank Model with Snow Component. *Research Note of the National Research Center for Disaster Prevention*, No. 65, 1–293
- Sugawara, M. (1995). Chapter 6: Tank model. In E. V. P. Singh (Ed.), *Computer models of Watershed hydrology*. Water Resources Publications, Littleton, Colo.
- Tessema, S. M. (2011). *Hydrological modeling as a tool for sustainable water resources management: a case study of the Awash River basin*. TRITA LWR.LIC 2056.

- Van Der Linden, S., & Woo, M. K. (2003). Transferability of hydrological model parameters between basins in data-sparse areas, subarctic Canada. *Journal of Hydrology*, 270(3–4), 182–194. [https://doi.org/10.1016/S0022-1694\(02\)00295-0](https://doi.org/10.1016/S0022-1694(02)00295-0)
- Vaze, J., Jordan, P., Beecham, R., Frost, A., & Summerell, G. (2011). *Guidelines for Rainfall-Runoff Modelling: Towards Best Practice Model Application* (Issue Interim Version 1.0). eWater Cooperative Research Centre 2011.
- Water. (2015, December). United Nations. <https://www.un.org/en/sections/issues-depth/water/index.html>
- Wickramaarachchi, T. N., Ishidaira, H., & Wijayarathna, T. M. N. (2012). An Application of Distributed Hydrological Model, YHyM/BTOPMC to Gin Ganga Watershed, Sri Lanka. *Engineer: Journal of the Institution of Engineers, Sri Lanka*, 45(2), 31. <https://doi.org/10.4038/engineer.v45i2.6939>
- Wijesekera, N. T. S. (1993). *Conceptual model structure development for streamflow simulation in the tropics*. University of Tokyo.
- Wijesekera, N. T. S. (2000). Parameter Estimation in Watershed Model: A Case Study Using Gin Ganga Watershed. *Transactions 2000, Annual Sessions of the Institution of Engineers of Sri Lanka, Volume 1(Part B)*, 26–32.
- Wijesekera, N. T. S. (2020). A streamflow threshold determination method for hydrologic model calibration and verification. *Engineer: Journal of the Institution of Engineers, Sri Lanka*, LIII(03), 1–18.
- Yokoo, Y., Kazama, S., Sawamoto, M., & Nishimura, H. (2001). Regionalization of lumped water balance model parameters based on multiple regression. *Journal of Hydrology*, 246(1–4), 209–222. [https://doi.org/10.1016/S0022-1694\(01\)00372-9](https://doi.org/10.1016/S0022-1694(01)00372-9)
- Young, A. R. (2006). Stream flow simulation within UK ungauged catchments using a daily rainfall-runoff model. *Journal of Hydrology*, 320(1–2), 155–172. <https://doi.org/10.1016/j.jhydrol.2005.07.017>