

The Impact of Cofferdamming and De-watering Cost on the Total Cost of Bridge Foundation

by

W.A.Gunaratne
 www.lib.mrt.ac.lk
Electronic Theses & Dissertations

**Department of Civil Engineering,
Faculty of Engineering,
University of Moratuwa,
Sri Lanka.**

The Impact of Cofferdamming and De-watering Cost on the Total Cost of Bridge Foundation

by

W.A.Gunaratne

පුස්තකාලය
මොරටුව විශ්ව විද්‍යාලය, ශ්‍රී ලංකාව
මොරටුව.

A project report submitted in partial fulfillment of the requirement for the
Degree of Master Engineering in Construction Management



October 1997

Supervised by Dr. N. D. Gunawardana

67982

um Thesis
coll.

Department of Civil Engineering,
Faculty of Engineering,
University of Moratuwa,
Sri Lanka.

624 "97"
624.003.2

67982



ACKNOWLEDGEMENT

In the first instance, I wish to extend my thanks to the Panel of Lecturers of Construction Management Division of the Civil Engineering Department, University of Moratuwa for conducting this valuable course in efficient and effective manner.

My special thanks to M/s M.B.S.Fernando and W.A.J.E.Fernando, Chairman and the Managing Director of RCDC for granting permission to use information /data pertaining to bridge construction sites executed by this company. Also I wish to express my sincere thanks to management of RCDC for sponsoring me for the construction management course.

I express my deep sense of gratitude for the able guidance and moral rendered by my supervisor, Dr.N.D.Gunawardana of the University of Moratuwa, without which this study would not have been successful.

I am most grateful to Mr.Y.S.K.Perera, who perused this report and prepare this report to suit for publication, and his suggestions for the improvement of the work have been very valuable.

Last but not least, I am grateful to all those who extended their co-operation and assistance to me in this study.

ABSTRACT

Over the last few decades the use of bridge design and construction technologies in Sri Lanka have been limited, except in respect of the projects funded by foreign aid. At present the general practice in bridge design is to adopt a number of standard bridge designs to suit the span, depth requirements of the particular site. No cost benefit analysis is done, to select from several possible alternatives. Traditional practices are adopted to select the type of bridge and bridge foundations. They do not explore the new technologies to design and construction. This report deals with a research work undertaken to study the cost of coffer damming and de-watering and the total bridge construction cost accordingly. Also this study identifies the percentages of construction cost of key items in relation to total construction cost.

In the selection of a suitable bridge for a given location the costs during construction are not usually considered. Particularly, the selection of a suitable foundation type does not consider the cost involved in cofferdamming and dewatering.

Usually in Sri Lanka, the cost of the superstructure of a bridge does not vary with the type of foundation used provided that the spans are the same.

Therefore, the total cost of a bridge for a given location is function of the type of foundation selected. The foundation types used in Sri Lanka are;

(a) Spread footings (b) Raft Foundations (c) Piles. (d) Well Foundations

However, experience shows that for any location all types of foundations cannot be used due to practical reasons. For example, pile foundations cannot be used for very low depths. Hence there are other factors influencing the type of foundation other than its total construction cost.

This study investigates the possibility of using the total construction cost including the cost of coffer damming and de-watering as the criterion for selection of foundation type. It also highlights the limitations of this approach in situations where other factors are more influential than the total construction cost.

Analysis of the eleven completed bridges yield the high proportion of foundations and substructure cost in relation to overall bridge construction costs. (In the order of 64.5%) It also indicates the low proportions (18.5%) of total construction costs of a bridge yields for super structure.

This study reveals that spread foundations are more suitable for the depth upto 4 meters. Caissons are the most expensive type of foundation for any depth. Also the study indicates action should be taken to review the sub structure and super structure design techniques and the choice of foundation types to minimize the construction costs of bridges.

TABLE OF CONTENTS

Page

1. INTRODUCTION	1
1.1 BACKGROUND.....	1
1.2 OBJECTIVES	2
1.3 METHODOLOGY.....	2
2. LITERATURE REVIEW	3
2.1 ROAD BRIDGES IN SRI LANKA	3
2.2 FACTORS INFLUENCING THE SELECTION OF APPROPRIATE BRIDGE	5
2.3 TYPE OF BRIDGE FOUNDATION.....	6
2.4 FACTORS INFLUENCING THE SELECTION OF APPROPRIATE BRIDGE FOUNDATION	9
2.5 CONSTRUCTION OF COFFERDAMS	13
2.6 DESIGN OF BRIDGES AND BRIDGE FOUNDATIONS IN SRI LANKA	14
2.7 COST BREAK DOWN OF SRI LANKAN BRIDGES.....	15
3. METHOD OF ANALYSIS AND COLLECTION OF DATA	21
3.1 INTRODUCTION	21
3.2 METHOD OF ANALYSIS.....	21
3.3 COLLECTION OF DATA	24
4. RESULTS AND OBSERVATIONS.....	28
4.1 INTRODUCTION	28
4.2 ESTIMATION OF FOUNDATION COST FOR DIFFERENT TYPES OF FOUNDATIONS FOR DIFFERENT AVERAGE DEPTHS	32
4.3 COMPARISON OF TOTAL COST OF FOUNDATION FOR DIFFERENT FOUNDATION TYPES FOR DIFFERENT AVERAGE DEPTHS.....	37
4.4 TOTAL COST ENVELOPS FOR DIFFERENT TYPES OF FOUNDATIONS	41
5. CONCLUSIONS AND RECOMMENDATIONS	43
5.1 CONCLUSIONS.....	43
5.2 RECOMMENDATIONS	46
6. REFERENCES.....	47
APPENDIX A	I
APPENDIX B	VI



University of Moratuwa, Sri Lanka
Electronic Theses & Dissertations
www.lib.mrt.ac.lk