

Determination of Bus Route Changes Required for the Improvement of Services at the Proposed Kadawatha Multimodal Transport Hub

R A M M Perera

University of Moratuwa, Sri Lanka

Amal S Kumarage

University of Moratuwa, Sri Lanka

Thivya P Amalan

University of Moratuwa, Sri Lanka

1. Introduction

Multimodality is the usage of several modes during a trip. A multimodal transport hub is a location where passengers transfer from one mode to another and facilitate the following functions:

- The act of changing between modes interchange
- The place where one changes between modes interchange zone
- A purpose-built facility to improve interchange quality interchange facility [1]

Kadawatha is a suburban town centre which is located 16 km away from the centre of Colombo in Gampaha District. Kadawatha city area is located in the Pahala Karagahamuna East, Pahala Karagahamuna North, Pahala Biyanwila East and Ihala Biyanwila North Grama Niladhari Divisions. Mahara Pradeshiya Sabha and Biyagama Pradeshiya Sabha are the administrative authorities of the Kadawatha town area. Ganemulla, Mahara, Kirillawala, Ranmuthugala, Dalupitiya, Karagahamuna (upper and lower), Biyanwila (upper and lower) and Kirimatiyagaraya are the smaller town centres surrounding Kadawatha.

There are some major problems in the existing Kadawatha bus terminal such as poor linkage with the main town centre and inadequate luxury facilities for passengers using expressway buses. Moreover, bus services to Ganemulla and Ragama terminate before reaching the town centre, the express and other regional services operating on the Kandy Road also do not touch the terminal due to such buses not using the by-pass. Absence of direct bus connections to destinations having high passenger demand such as Wattala, Weliweriya is also a notable shortcoming.

2. Methodology

Household Visits Surveys (HVS) and Bus Volume Counts (BVC) data of Colombo Transport Master Plan (University of Moratuwa, 2015) were used as secondary data for this research. The multimodal hub plan being developed by the University of Moratuwa was examined using JICA STRADA, a software for bus passenger demand modelling with GIS mapping to study the current condition of the route network by comparing supply and demand data.




Figure 1: Existing Direct connections and trip attraction and distribution by TAZ to Kadawatha

3. Results

Figure 1 shows the direct connections available and trip attraction and distribution from each Transport Analysis Zone (TAZ) to and from Kadawatha. High demand for direct connections to Kadawatha can be observed from Weliweriya, Wattala, Kelaniya and Battaramulla among others, none of which are currently connected directly to Kadawatha.

Figure 2 shows the TAZ centroids which can be connected via direct links from Kadawatha according to passenger demand. The new route can be established to cater to passenger demand from the Battaramulla, Thalawathugoda and Malabe areas through Hokandara interchange. Further services can be established to directly connect areas such as Wattala, Kelaniya and Weliweriya as shown in the above graph. Those direct connections could be an advantage for Kadawatha to function as a hub for that area.




Figure 2: Proposed Direct connections from TAZ Zone Centroids to Kadawatha

3.1. Proposals for new routes

3.1.1. Route overlapping [2]

Passengers have to use the following combination of bus routes to reach Kelaniya from Kadawatha: first, Kadawatha - Kiribathgoda (along routes 138, 193 or 154, or via long distance bus) and then the Kiribathgoda – Pettah route via Kelaniya.

Of these, routes 138, 193 and 154 cannot be changed due to high passenger demand for the status quo. However, the Kiribathgoda - Pettah route can be extended to Kadawatha as an overlapping route to other routes such as 138 and 193.

3.1.2. Route Merging

There are various routes to Ragama from Kadawatha such as 222, 325, 326, 327, 327/1, 222/1 and 815. But passengers are compelled to take buses plying the Kadawatha-Ragama and later the Ragama-Pettah (via Wattala) routes in order to reach Wattala. Therefore, the Ragama-Wattala route and one of the above routes between Ragama and Kadawatha can be merged to establish a direct route to Wattala from Kadawatha. This paper recommends that route 222 is merged with the Ragama-Pettah route, considering passenger demand.

It is also recommended to add Kadawatha-Battaramulla and Kadawatha-Weliweriya as new routes.

Comparison: Doing Nothing vs Implementing New Direct Connections




Figure 3: Passenger Demand by link in the Do-Nothing Scenario (DNS)

The passenger volumes got through the STRADA analysis by each link in the existing network without implementing new links are shown in figure 3. The highest passenger volumes can be seen along the Kandy Road Corridor which are expected to be attracted to the new hub due to direct connections.

Increments in total passenger, total passenger hours and total passenger kms

after implementing the new direct connections to Kadawatha from high passenger demand centres such as Wattala, Weliweriya and Battramulla can be seen along many routes (Table 1). A significant increment in total passenger numbers (1,067)

additional passengers) can be seen on the 261 route, while the average total increment along other routes is of 200 additional passengers. These values show a higher level of network improvement with route adjustments alone, do not require the introduction of new modes or of major structural changes to the network.

Table 1: Comparison of Total passengers, Total passenger hours and Total passenger kms by route in DNS and After Scenario

| | DNS (bi-direction) | | | After Scenario (bi-direction) | | |
|--------------------------------------|---------------------|-----------------------------|---------------------------|-------------------------------|-----------------------------|---------------------------|
| Route Number | Total Passengers | Total passenger hours | Total passenger kms | Total Passengers | Total passenger hours | Total passenger kms |
| 154 (Kadawatha- Bambalapitiya) | 50,967 | 22,448 | 224,593 | 50,971 | 22,408 | 224,164 |
| 222 (Kadawatha- Ragama) | 6,846 | 2,209 | 22,121 | 6,677 | 2,159 | 21,624 |
| 222_1 (Kadawatha- Ragama) | 10,265 | 2,365 | 23,742 | 10,364 | 2,362 | 23,703 |
| 223 (Kadawatha- Ganemulla) | 9,036 | 3,661 | 36,643 | 9,105 | 3,678 | 36,814 |
| 223R | 13,075 | 5,812 | 58,164 | 13,154 | 5,863 | 58,664 |
| 261 (Mahara-Pettah) | 44,277 | 20,622 | 20,6495 | 45,344 | 21,151 | 211,814 |
| 327_1 (Kadawatha- Ragama) | 1,199 | 299 | 3,054 | 1,195 | 301 | 3,065 |
| KAD_WAT (Kadawatha- Wattala) | | | | 591 | 243 | 2,464 |
| KAD_WEL (Kadawatha- Weliweriya) | | | | 1,032 | 790 | 8,008 |
| KAD_BAT (Kadawatha- Battaramulla) | | | | 353 | 183 | 1,898 |

Maximum passengers per hour per Direction (PPHPD) values in Table 2 further confirm the improvement to the network with the new routes. The Kadawatha-Wattala route shows the highest PPHPD amongst newly introduced routes. An average PPHPD of 70 along these new routes confirms the adequacy of passenger demand for these operations.

Table 2: Comparison of Passengers per Hour per Direction (PPHPD) by route in Do Nothing Scenario and After Implementation Scenario

| Route Number | Max PPHPD (Do nothing Case) | PPHPD (After adding New routes) | Remarks |
|----------------------------------|-----------------------------------|---------------------------------------|--------------------------|
| 261(Mahara-Pettah) | 1600 | 1600 | Extended to Kadawatha |
| 325(Kdawatha- Ragama) | 800 | 800 | |
| 327/1 (Kadawatha- Ragama) | 100 | 100 | |
| 222(Kadawatha -Ragama) | 500 | 400 | |
| 222/1 (Kadawatha -Ragama) | 1100 | 1100 | |
| 223 (Kadawatha - Ganemulla) | 1500 | 1000 | |
| 138 (Kadawatha - Fort) | 1000 | 1000 | |
| 138_1 (Kirillawala -Fort) | 300 | 300 | |
| 154 (Kadawatha -Bambalapitiya) | 1600 | 1600 | |
| 193 (Kadawatha -Townhall) | 800 | 800 | |
| KAD_WAT (Kadawatha -Wattala) | | 100 | New Route |
| KAD_WEL (Kadawatha -Weliweriya) | | 65 | New Route |
| KAD_BAT (Kadwatha -Battaramulla) | | 42 | New Route |

5. Conclusions and Recommendations

There are areas with high passenger demand such as Kelaniya and Weliweriya, both situated in proximity to Kadawatha, and which, though lacking direct connections currently, can be directly connected to Kadawatha. Overlap of existing routes such as the Kiribathgoda-Pettah route and route merging can be used to provide a larger number of direct connections to Kadawatha from high-demand areas. Significant improvement of the network with respect to total passenger numbers and passenger hours would be observed upon implementation of these small changes.

6. References

- [1] Gargi Gosh (2011). Formulation of framework and guideline for multimodal transport hub.
- [2] Sirisoma R.M.N.T., Bandara J.M.S.J., Kumarage A.S. Development of a methodology for bus route network plan for the western province. Sri Lanka.