

REFERENCES

- [1] D. Y. Pimenov *et al.*, “Resource saving by optimization and machining environments for sustainable manufacturing: A review and future prospects,” *Renew. Sustain. Energy Rev.*, vol. 166, p. 112660, Sep. 2022.
- [2] A. M. Khorasani, M. R. S. Yazdi, and M. S. Safizadeh, “Analysis of machining parameters effects on surface roughness: a review,” *Int. J. Comput. Mater. Sci. Surf. Eng.*, vol. 5, no. 1, p. 68, 2012.
- [3] S. Şap, Ü. A. Usca, M. Uzun, M. Kuntoğlu, E. Salur, and D. Y. Pimenov, “Investigation of the Effects of Cooling and Lubricating Strategies on Tribological Characteristics in Machining of Hybrid Composites,” *Lubricants*, vol. 10, no. 4, Apr. 2022.
- [4] R. K. Singh, A. K. Sharma, A. R. Dixit, A. K. Tiwari, A. Pramanik, and A. Mandal, “Performance Evaluation of Alumina-graphene Hybrid Nano-cutting Fluid in Hard Turning,” *J. Clean. Prod.*, 2017.
- [5] G. Hao and Z. Liu, “The heat partition into cutting tool at tool-chip contact interface during cutting process: a review,” *Int. J. Adv. Manuf. Technol. 2020 1081*, vol. 108, no. 1, pp. 393–411, May 2020.
- [6] J. Singh, S. S. Gill, M. Dogra, and R. Singh, “A review on cutting fluids used in machining processes,” *Eng. Res. Express*, vol. 3, no. 1, p. 12002, Mar. 2021.
- [7] P. Pranav, E. Sneha, and S. Rani, “Vegetable oil-based cutting fluids and its behavioral characteristics in machining processes: a review,” *Ind. Lubr. Tribol.*, vol. 73, no. 9, pp. 1159–1175, 2021.
- [8] V. S. Sharma, G. Singh, and K. Sorby, “A Review on Minimum Quantity Lubrication for Machining Processes,” <http://dx.doi.org/10.1080/10426914.2014.994759>, vol. 30, no. 8, pp. 935–953, Aug. 2015.

- [9] Y. Shokoohi, E. Khosrojerdi, and B. H. Rassolian Shiadhi, "Machining and ecological effects of a new developed cutting fluid in combination with different cooling techniques on turning operation," *J. Clean. Prod.*, vol. 94, pp. 330–339, 2015.
- [10] A. K. Sharma, A. K. Tiwari, and A. R. Dixit, "Effects of Minimum Quantity Lubrication (MQL) in machining processes using conventional and nanofluid based cutting fluids: A comprehensive review," *J. Clean. Prod.*, vol. 127, pp. 1–18, Jul. 2016.
- [11] V. Vasu and G. P. K. Reddy, "Effect of minimum quantity lubrication with Al₂O₃ nanoparticles on surface roughness, tool wear and temperature dissipation in machining Inconel 600 alloy," vol. 225, pp. 3–15, 2011.
- [12] R. Padmini, P. V. Krishna, and G. K. Mohana, "Author's Accepted Manuscript," *Tribology Int.*, 2015.
- [13] M. M. A. Khan, M. A. H. Mithu, and N. R. Dhar, "Effects of minimum quantity lubrication on turning AISI 9310 alloy steel using vegetable oil-based cutting fluid," *J. Mater. Process. Technol.*, vol. 209, no. 15–16, pp. 5573–5583, 2009.
- [14] C. H. R. V. Kumar and B. Ramamoorthy, "Performance of coated tools during hard turning under minimum fluid application," vol. 185, pp. 210–216, 2007.
- [15] M. C. Kang, K. H. Kim, S. H. Shin, S. H. Jang, J. H. Park, and C. Kim, "Surface & Coatings Technology Effect of the minimum quantity lubrication in high-speed end-milling of AISI D2 cold-worked die steel (62 HRC) by coated carbide tools," vol. 202, pp. 5621–5624, 2008.
- [16] N. R. Dhar, M. Kamruzzaman, and M. Ahmed, "Effect of minimum quantity lubrication (MQL) on tool wear and surface roughness in turning AISI-4340 steel," vol. 172, pp. 299–304, 2006.
- [17] S. Chinchankar, H. M. Bawangaonwala, and S. Bokade, "Investigations on the

Machining Performance using Solid Lubricant Mixed with Varying Proportions in Vegetable Oil during Hard Turning Investigations on the Machining Performance using Solid Lubricant Mixed with Varying Proportions in Vegetable Oil during ,” 2020.

- [18] P. Taylor, S. K. Das, S. U. S. Choi, and H. E. Patel, “Heat Transfer in Nanofluids — A Review Heat Transfer in Nanofluids —,” no. July 2012, pp. 37–41, 2007.
- [19] R. J. Aitken, M. Q. Chaudhry, A. B. A. Boxall, and M. Hull, “Manufacture and use of nanomaterials : current status in the UK and global trends,” pp. 300–306, 2015.
- [20] I. Khan, K. Saeed, and I. Khan, “Nanoparticles: Properties, Applications and Toxicities,” *Arab. J. Chem.*, no. May, 2017.
- [21] P. B. Patole, V. V. Kulkarni, and S. G. Bhatwadekar, “MQL Machining with nano fluid: a review,” *Manuf. Rev.*, vol. 8, p. 13, 2021.
- [22] K. A. Hamid, W. H. Azmi, M. F. Nabil, R. Mamat, and K. V Sharma, “International Journal of Heat and Mass Transfer Experimental investigation of thermal conductivity and dynamic viscosity on nanoparticle mixture ratios of TiO₂ -SiO₂ nanofluids Society of Automotive Engineers,” *Int. J. Heat Mass Transf.*, vol. 116, pp. 1143–1152, 2018.
- [23] H. Nanofluids, F. Amini, S. Z. Miry, A. Karimi, and M. Ashjaee, “Experimental Investigation of Thermal Conductivity and Viscosity of SiO₂ / Multiwalled Carbon Nanotube,” pp. 3398–3407, 2019.
- [24] Z. A. Wahaizad Safiei^{1,*}, Md Mustafizur Rahman², Ratnakar Kulkarni³, Md Noor Ariffin⁴ and A. Malek², “Thermal Conductivity and Dynamic Viscosity of Nanofluids : A Review,” vol. 2, no. 2, pp. 66–84, 2020.
- [25] R. Sankaranarayanan, R. Jesudoss, N. Hynes, S. K. J, and G. M. Krolczyk, “A comprehensive review on research developments of vegetable-oil based cutting fluids for sustainable machining challenges,” *J. Manuf. Process.*, vol. 67, no.

November 2020, pp. 286–313, 2021.

- [26] S. Debnath, M. M. Reddy, and Q. S. Yi, “Environmental friendly cutting fluids and cooling techniques in machining: a review,” *J. Clean. Prod.*, vol. 83, pp. 33–47, Nov. 2014.
- [27] R. Katna, K. Singh, N. Agrawal, and S. Jain, “Green Manufacturing – Performance of a Biodegradable Cutting Fluid,” vol. 6914, no. May, 2017.
- [28] T. Norrby and T. Norrby, “Feature Environmentally adapted lubricants – where are the opportunities ?,” 2015.
- [29] A. K. Singh and A. K. Gupta, “Metalworking fluids from vegetable oils,” no. September, pp. 167–176, 2006.
- [30] T. P. Jeevan and S. R. Jayaram, “Tribological Properties and Machining Performance of Vegetable Oil Based Metal Working Fluids — A Review,” pp. 42–65, 2018.
- [31] G. I. P. Perera, H. M. C. M. Herath, I. M. S. J. Perera, and M. G. H. M. M. P. Medagoda, “Investigation on white coconut oil to use as a metal working fluid during turning:,” <http://dx.doi.org/10.1177/0954405414525610>, vol. 229, no. 1, pp. 38–44, Apr. 2014.
- [32] D. A. and S. M. A. A. N. Perera G. I., “Investigation on white coconut oil to use as a metal working fluid during turning,” vol. 229, no. 1, pp. 38–44, 2015.
- [33] K. C. Wickramasinghe, H. M. C. M. Herath, and G. I. P. Perera, “Empirical investigation of surface quality and temperature during turning AISI 304 steel with vegetable oil based metalworking fluids,” no. October, pp. 1–4, 2016.
- [34] K. C. Wickramasinghe, G. I. P. Perera, and H. M. C. M. Herath, “Formulation and performance evaluation of a novel coconut oil–based metalworking fluid,” <http://dx.doi.org/10.1080/10426914.2016.1257858>, vol. 32, no. 9, pp. 1026–1033, Jul. 2017.

- [35] K. C. Wickramasinghe, G. I. P. Perera, S. W. M. A. I. Senevirathne, H. K. Punchihewa, and H. Sasahara, "Surface quality evaluation of 0.2 % C and AISI 304 steels in turning with sustainable lubricating condition," *J. Mech. Sci. Technol.*, vol. 33, no. 12, pp. 5753–5759, Dec. 2019.
- [36] W. L. R. Fernando, N. Sarmilan, K. C. Wickramasinghe, H. M. C. M. Herath, and G. I. P. Perera, "Experimental investigation of Minimum Quantity Lubrication (MQL) of coconut oil based Metal Working Fluid," *Mater. Today Proc.*, vol. 23, pp. 23–26, Jan. 2020.
- [37] H. Babar, "Towards hybrid nanofluids : Preparation , thermophysical properties , applications , and challenges Towards hybrid nano fl uids: Preparation , thermophysical properties , applications , and challenges," *J. Mol. Liq.*, vol. 281, no. March, pp. 598–633, 2019.
- [38] V. S. Sharma, M. Dogra, and N. M. Suri, "Cooling techniques for improved productivity in turning," *Int. J. Mach. Tools Manuf.*, vol. 49, no. 6, pp. 435–453, May 2009.
- [39] K. K. Gajrani, P. S. Suvin, S. V. Kailas, and M. R. Sankar, "Hard machining performance of indigenously developed green cutting fluid using flood cooling and minimum quantity cutting fluid," *J. Clean. Prod.*, vol. 206, pp. 108–123, 2019.
- [40] S. Debnath, M. M. Reddy, and Q. S. Yi, "AC SC," *J. Clean. Prod.*, 2014.
- [41] "A Critical review on Minimum Quantity Lubrication (MQL) Coolant System for Machining Operations System for Machining Operations," no. November, 2016.
- [42] E. O. Ezugwu and A. Force, *Overview of the Machining of Titanium Alloys*, vol. 2. Elsevier, 2017.
- [43] S. Chinchankar, S. S. Kore, and P. Hujare, "A review on nanofluids in minimum quantity lubrication machining," vol. 68, no. May, pp. 56–70, 2021.
- [44] H. H. Al-kayiem, S. C. Lin, and A. Lukmon, "Review on Nanomaterials for

Thermal Energy Storage Technologies Review on Nanomaterials for Thermal Energy Storage Technologies,” no. September, 2013.

- [45] P. V. Krishna, R. R. Srikant, and D. N. Rao, “International Journal of Machine Tools & Manufacture Experimental investigation on the performance of nanoboric acid suspensions in SAE-40 and coconut oil during turning of AISI 1040 steel,” *Int. J. Mach. Tools Manuf.*, vol. 50, no. 10, pp. 911–916, 2010.
- [46] M. M. S. Prasad and R. R. Srikant, “PERFORMANCE EVALUATION OF NANO GRAPHITE INCLUSIONS IN CUTTING FLUIDS WITH MQL TECHNIQUE IN TURNING OF AISI 1040,” pp. 381–393, 2013.
- [47] N. Saravanakumar, L. Prabu, M. Karthik, and A. Rajamanickam, “Experimental analysis on cutting fluid dispersed with silver nano particles,” *J. Mech. Sci. Technol.*, vol. 28, no. 2, pp. 645–651, 2014.
- [48] R. Padmini, P. V. Krishna, and G. K. M. Rao, “Proceedings of the Institution of Mechanical Engineers , Part B : Journal of Engineering Manufacture,” 2014.
- [49] A. Kumar, R. Kumar, A. Rai, and A. Kumar, “ScienceDirect Characterization and experimental investigation of Al₂O₃ nanoparticle based cutting fluid in turning of AISI 1040 steel under minimum quantity lubrication (MQL),” *Mater. Today Proc.*, vol. 3, no. 6, pp. 1899–1906, 2016.
- [50] A. Kumar, A. Kumar, R. Kumar, and A. Rai, “ScienceDirect Tribological Investigation of TiO₂ Nanoparticle based Cutting Fluid in Machining under Minimum Quantity Lubrication (MQL),” *Mater. Today Proc.*, vol. 3, no. 6, pp. 2155–2162, 2016.
- [51] M. K. Gupta, P. K. Sood, and V. S. Sharma, “SC,” *J. Clean. Prod.*, 2016.
- [52] B. C. Behera, S. Ghosh, and P. V Rao, “Tribology International Application of nano fluids during minimum quantity lubrication : A case study in turning process,” vol. 101, pp. 234–246, 2016.

- [53] R. A. Raju, A. Andhare, and N. K. Sahu, "Performance of multi-walled carbon nanotube-based nanofluid in turning operation," <http://dx.doi.org/10.1080/10426914.2017.1279291>, vol. 32, no. 13, pp. 1490–1496, Oct. 2017.
- [54] B. C. Behera, D. Setti, S. Ghosh, and P. V. Rao, "Spreadability studies of metal working fluids on tool surface and its impact on minimum amount cooling and lubrication turning," *J. Mater. Process. Tech.*, 2017.
- [55] M. Ukamanal, P. Chandra, and A. Kumar, "ScienceDirect Temperature distribution during AISI 316 steel turning under TiO₂-water based nanofluid spray environments," *Mater. Today Proc.*, vol. 5, no. 9, pp. 20741–20749, 2018.
- [56] K. Kishore and R. K. Behera, "Effect of minimum quantity lubrication with Al₂O₃ Nanofluid on Surface Roughness and its prediction using hybrid fuzzy controller in turning operation of Inconel 600," *Mater. Today Proc.*, vol. 5, no. 9, pp. 20660–20668, 2018.
- [57] M. Nouby, "ScienceDirect ScienceDirect ScienceDirect Application of Taguchi-Response surface analysis to optimize the Application of Taguchi-Response surface X-750 analysis to optimize the cutting parameters on turning of Inconel using Nanofluids Engineering on cutt," *Procedia Manuf.*, vol. 30, pp. 90–97, 2019.
- [58] Ç. V. Yıldırım, M. Sarıkaya, T. Kıvak, and Ş. Şirin, "The effect of addition of hBN nanoparticles to nanofluid-MQL on tool wear patterns, tool life, roughness and temperature in turning of Ni-based Inconel 625," *Tribol. Int.*, 2019.
- [59] K. Venkatesan, S. Devendiran, N. M. Ghazaly, R. Rahul, and T. Mughilan, "Optimization of Cutting Parameters on turning of Incoloy 800H Optimization of Cutting Parameters on turning of Incoloy 800H using Al Nanofluid in Coconut using Al Nanofluid in Coconut oil Costing models for capaci," *Procedia Manuf.*, vol. 30, pp. 268–275, 2019.

- [60] Ç. V. Yıldırım, “Experimental comparison of the performance of nanofluids, cryogenic and hybrid cooling in turning of Inconel 625,” *Tribol. Int.*, 2019.
- [61] R. Kumar, A. K. Sahoo, P. C. Mishra, and R. K. Das, “Influence of Al₂O₃ and TiO₂ nanofluid on hard turning performance,” 2019.
- [62] M. Khajezadeh, J. Moradpour, and M. R. Razfar, “Influence of nanolubricant particles ’ size on flank wear in hard turning,” *Mater. Manuf. Process.*, vol. 0, no. 0, pp. 1–8, 2019.
- [63] T. Eli, “Tuning nanofluids for improved lubrication performance in turning biomedical grade titanium alloy,” *J. Clean. Prod.*, 2018.
- [64] A. Das, S. K. Patel, and S. R. Das, “Performance comparison of vegetable oil based nano fluids towards machinability improvement in hard turning of HSLA steel using minimum quantity lubrication,” vol. 506, 2019.
- [65] M. K. Gupta *et al.*, “Performance Evaluation of Vegetable Oil-Based Nano-Cutting Fluids in Environmentally Friendly Machining of Inconel-800 Alloy,” 2019.
- [66] K. Park and B. Ewald, “Effect of Nano-Enhanced Lubricant in Minimum Quantity Lubrication Balling Milling,” vol. 133, no. July, pp. 1–8, 2011.
- [67] M. S. Najiha and M. M. Rahman, “Experimental investigation of flank wear in end milling of aluminum alloy with water-based TiO₂ nanofluid lubricant in minimum quantity lubrication technique,” 2016.
- [68] M. S. Najiha, M. M. Rahman, and K. Kadirgama, *Performance of water-based TiO₂ nanofluid during the minimum quantity lubrication machining of aluminium alloy, AA6061-T6*. Elsevier Ltd, 2016.
- [69] A. Uysal, F. Demiren, and E. Altan, “Applying Minimum Quantity Lubrication (MQL) Method on Milling of Martensitic Stainless Steel by Using Nano Mos₂ Reinforced Vegetable Cutting Fluid,” *Procedia - Soc. Behav. Sci.*, vol. 195, pp. 2742–2747, 2015.

- [70] Ş. Şirin and T. Kivak, “Performances of different eco-friendly nanofluid lubricants in the milling of Inconel X-750 superalloy,” *Tribol. Int.*, 2019.
- [71] B. Sen, M. Mia, U. K. Mandal, and S. P. Mondal, “Synergistic effect of silica and pure palm oil on the machining performances of Inconel 690: A study for promoting minimum quantity nano doped-green lubricants,” *J. Clean. Prod.*, p. 120755, 2020.
- [72] W. Huang, D. Wu, and J. Chen, “Robust design of using nanofluid / MQL in micro-drilling,” pp. 1–7, 2015.
- [73] S. Singh, A. Pal, and T. Singh, “Performance evaluation of aluminium 6063 drilling under the influence of nano fluid minimum quantity lubrication,” vol. 137, pp. 537–545, 2016.
- [74] A. Garg, S. Sarma, B. N. Panda, J. Zhang, and L. Gao, “Study of effect of nano fluid concentration on response characteristics of machining process for cleaner production,” *J. Clean. Prod.*, vol. 135, pp. 476–489, 2016.
- [75] H. Salimi-yasar, S. Z. Heris, M. Shanbedi, A. Amiri, and A. Kameli, “SC,” *Powder Technol.*, 2016.
- [76] H. Salimi-yasar, S. Zeinali, and M. Shanbedi, “Tribology International Influence of soluble oil-based TiO₂ nano fluid on heat transfer performance of cutting fluid,” no. December 2016, 2017.
- [77] S. Muthuvel, M. N. Babu, and N. Muthukrishnan, “Copper nanofluids under minimum quantity lubrication during drilling of AISI 4140 steel,” *Aust. J. Mech. Eng.*, vol. 0, no. 0, pp. 1–14, 2018.
- [78] V. Shalimba and B. Sopko, “Nanofluids Application in the Drilling Process Introduction Samples Preparation and Characterizations,” *Manuf. Technol.*, vol. 18, no. 3, pp. 493–498, 2018.
- [79] A. M. Centre, F. K. Pembuatan, U. Teknikal, H. T. Jaya, and G. District,

- “Experimental Investigation of Drilling Process using Nanofluid as Coolant Journal of Advanced Manufacturing Technology (JAMT),” pp. 11–22, 2018.
- [80] J. Nam and S. W. Lee, “Machinability of Titanium Alloy (Ti-6Al-4V) in Environmentally-Friendly Micro-Drilling Process with Nanofluid Minimum Quantity Lubrication Using Nanodiamond Particles,” vol. 5, no. 1, pp. 29–35, 2018.
- [81] J. Soo, P. Lee, and S. Won, “International Journal of Machine Tools & Manufacture Experimental characterization of micro-drilling process using nanofluid minimum quantity lubrication,” *Int. J. Mach. Tools Manuf.*, vol. 51, no. 7–8, pp. 649–652, 2011.
- [82] W. T. Huang, D. H. Wu, and J. T. Chen, “Robust design of using nanofluid/MQL in micro-drilling,” *Int. J. Adv. Manuf. Technol.*, vol. 85, no. 9–12, pp. 2155–2161, 2016.
- [83] H. Salimi-Yasar, S. Zeinali Heris, M. Shanbedi, A. Amiri, and A. Kameli, “Experimental investigation of thermal properties of cutting fluid using soluble oil-based TiO₂ nanofluid,” *Powder Technol.*, vol. 310, pp. 213–220, Apr. 2017.
- [84] K. H. Park, B. Ewald, and P. Y. Kwon, “Effect of nano-enhanced lubricant in minimum quantity lubrication balling milling,” *J. Tribol.*, vol. 133, no. 3, Jul. 2011.
- [85] M. Amrita and S. A. Shariq, “Experimental investigation on application of emulsifier oil based nano cutting fluids in metal cutting process,” *Procedia Eng.*, vol. 97, pp. 115–124, 2014.
- [86] R. Padmini, P. Vamsi Krishna, and G. Krishna Mohana Rao, “Effectiveness of vegetable oil based nanofluids as potential cutting fluids in turning AISI 1040 steel,” *Tribol. Int.*, vol. 94, pp. 490–501, Feb. 2016.
- [87] M. K. Gupta, P. K. Sood, and V. S. Sharma, “Optimization of machining parameters and cutting fluids during nano-fluid based minimum quantity lubrication turning of titanium alloy by using evolutionary techniques,” *J. Clean.*

Prod., vol. 135, pp. 1276–1288, Nov. 2016.

- [88] A. K. Sharma, A. K. Tiwari, A. R. Dixit, and R. K. Singh, “Investigation into Performance of SiO₂ Nanoparticle Based Cutting Fluid in Machining Process,” *Mater. Today Proc.*, vol. 4, no. 2, pp. 133–141, 2017.
- [89] Chetan, B. C. Behera, S. Ghosh, and P. V. Rao, “Application of nanofluids during minimum quantity lubrication: A case study in turning process,” *Tribol. Int.*, vol. 101, pp. 234–246, Sep. 2016.
- [90] Ç. V. Yıldırım, “Experimental comparison of the performance of nanofluids, cryogenic and hybrid cooling in turning of Inconel 625,” *Tribol. Int.*, vol. 137, pp. 366–378, Sep. 2019.
- [91] K. Venkatesan, S. Devendiran, N. M. Ghazaly, and Nishanth, “Application of Taguchi-Response surface analysis to optimize the cutting parameters on turning of Inconel X-750 using Nanofluids suspended Al₂O₃ in coconut oil,” *Procedia Manuf.*, vol. 30, pp. 90–97, Jan. 2019.
- [92] J. W. Kim *et al.*, “Parametric analysis and optimization of nanofluid minimum quantity Parametric analysis and optimization of nanofluid minimum quantity lubrication micro-drilling process for titanium Conference alloy lubrication mi,” *Procedia Manuf.*, vol. 26, pp. 403–414, 2018.
- [93] S. S. Rahman, M. Z. I. Ashraf, A. N. Amin, M. S. Bashar, M. F. K. Ashik, and M. Kamruzzaman, “Tuning nanofluids for improved lubrication performance in turning biomedical grade titanium alloy,” *J. Clean. Prod.*, vol. 206, pp. 180–196, Jan. 2019.
- [94] H. A. Kishawy, H. Hegab, and I. Deiab, “Sustainability Assessment during Machining Ti-6Al-4V with Nano-Additives-Based Minimum Quantity Lubrication,” 2019.
- [95] M. K. Gupta *et al.*, “Performance Evaluation of Vegetable Oil-Based Nano-Cutting

Fluids in Environmentally Friendly Machining of Inconel-800 Alloy,” 2019.

- [96] V. Vasu and G. P. K. Reddy, “Effect of minimum quantity lubrication with Al₂O₃ nanoparticles on surface roughness, tool wear and temperature dissipation in machining Inconel 600 alloy,” <http://dx.doi.org/10.1177/1740349911427520>, vol. 225, no. 1, pp. 3–15, Nov. 2011.
- [97] H. Hegab, H. A. Kishawy, M. H. Gadallah, U. Umer, and I. Deiab, “On machining of Ti-6Al-4V using multi-walled carbon nanotubes-based nano-fluid under minimum quantity lubrication,” 2018.
- [98] T. Jadam, M. Rakesh, S. Datta, and N. Mql, “Machinability of Ti – 6Al – 4V Superalloy : Performance of Dry Cutting and Nanofluid MQL (MWCNT-Added Rice Bran Oil),” *Arab. J. Sci. Eng.*, 2020.
- [99] S. Sarkar and S. Datta, “Machining Performance of Inconel 718 Under Dry , MQL , and Nanofluid MQL Conditions : Application of Coconut Oil (Base Fluid) and Multi-walled Carbon Nanotubes as Additives,” *Arab. J. Sci. Eng.*, vol. 718, 2020.
- [100] S. Kumar *et al.*, “An Investigation Of Multi Walled Carbon Nanotubes Based Nano Cutting Fluids In Turning Of Martensitic Stainless Steel By Using Taguchi And Anova Analysis,” pp. 08–15.
- [101] H. Hegab, U. Umer, M. Soliman, and H. A. Kishawy, “Effects of nano-cutting fluids on tool performance and chip morphology during machining Inconel 718,” *Int. J. Adv. Manuf. Technol.*, vol. 96, no. 9–12, pp. 3449–3458, 2018.
- [102] M. A. Makhesana and K. M. Patel, “Performance assessment of vegetable oil-based nanofluid in Minimum Quantity Lubrication (MQL) during machining of Inconel 718,” *Adv. Mater. Process. Technol.*, vol. 0, no. 0, pp. 1–17, 2021.
- [103] P. Rapeti, V. K. Pasam, K. M. Rao Gurrum, and R. S. Revuru, “Performance evaluation of vegetable oil based nano cutting fluids in machining using grey relational analysis-A step towards sustainable manufacturing,” *J. Clean. Prod.*, vol.

172, pp. 2862–2875, 2016.

- [104] Y. Wang *et al.*, “Processing Characteristics of Vegetable Oil-based Nanofluid MQL for Grinding Different Workpiece Materials,” *Int. J. Precis. Eng. Manuf. - Green Technol.*, vol. 5, no. 2, pp. 327–339, 2018.
- [105] T. M. Duc, T. T. Long, and T. Q. Chien, “Performance evaluation of MQL parameters using Al₂O₃ and MoS₂ nanofluids in hard turning 90CrSi steel,” *Lubricants*, vol. 7, no. 5, 2019.
- [106] K. R. Wattoo, “A Novel Study on The Effects of Minimum Quantity Lubrication and Machining Parameters in Turning of Ti-6Al-4V Alloy By Applying Al₂O₃-Graphene Hybrid Nanoparticle Enriched Cutting Fluid,” pp. 1–15, 2021.
- [107] M. Jamil *et al.*, “Effects of hybrid Al₂O₃-CNT nanofluids and cryogenic cooling on machining of Ti-6Al-4V,” *Int. J. Adv. Manuf. Technol.*, vol. 102, no. 9–12, pp. 3895–3909, 2019.
- [108] M. Sandeep Kumar and V. Murali Krishna, “An Investigation on Turning AISI 1018 Steel with Hybrid Biodegradable Nanofluid/MQL Incorporated with Combinations of CuO-Al₂O₃ Nanoparticles,” *Mater. Today Proc.*, vol. 24, pp. 1577–1584, 2020.
- [109] S. Gugulothu and V. K. Pasam, “Experimental investigation to study the performance of CNT/MoS₂ hybrid nanofluid in turning of AISI 1040 steel,” *Aust. J. Mech. Eng.*, vol. 0, no. 0, pp. 1–11, 2020.
- [110] S. Chinchankar, S. S. Kore, and P. Hujare, “A review on nanofluids in minimum quantity lubrication machining,” *J. Manuf. Process.*, vol. 68, no. PA, pp. 56–70, 2021.
- [111] K. A. Sharma, A. K. Tiwari, and A. R. Dixit, “Mechanism of Nanoparticles Functioning and Effects in Machining Processes: A Review,” *Mater. Today Proc.*, vol. 2, no. 4–5, pp. 3539–3544, Jan. 2015.

- [112] A. K. Sharma, A. K. Tiwari, and A. R. Dixit, "Progress of Nanofluid Application in Machining: A Review," <https://doi.org/10.1080/10426914.2014.973583>, vol. 30, no. 7, pp. 813–828, Jul. 2015.
- [113] A. Kotia, P. Rajkhowa, G. S. Rao, and S. K. Ghosh, "Thermophysical and tribological properties of nanolubricants: A review," *Heat Mass Transf. und Stoffuebertragung*, vol. 54, no. 11, pp. 3493–3508, 2018.
- [114] I. O. P. C. Series and M. Science, "Effect of TiO₂ and Al₂O₃ -ethylene glycol-based nanofluids on cutting temperature and surface roughness during turning process of AISI 1018 Effect of TiO₂ and Al₂O₃ -ethylene glycol-based nanofluids on cutting temperature and surface roughness dur," 2020.
- [115] I. O. P. C. Series and M. Science, "An overview on performance of metal working fluids with enrichment of nanoparticles for machining process An overview on performance of metal working fluids with enrichment of nanoparticles for machining process," 2018.
- [116] R. Kumar, S. Amit, R. Dixit, A. Mandal, and A. Kumar, "Emerging application of nanoparticle - enriched cutting fluid in metal removal processes : a review," 2017.
- [117] M. Saravana Kumar and K. L. Senthil Kumar, "An Investigation Of Multi Walled Carbon Nanotubes Based Nano Cutting Fluids In Turning Of Martensitic Stainless Steel By Using Taguchi And Anova Analysis," *IOSR J. Mech. Civ. Eng.*, vol. 15, no. 7, pp. 8–15, 2014.
- [118] A. Raihan, I. Ali, and B. Salam, "A review on nanofluid : preparation , stability , thermophysical properties , heat transfer characteristics and application," no. August, 2020.
- [119] A. M. Khorasani, M. R. S. Yazdi, and M. S. Safizadeh, "Analysis of machining parameters effects on surface roughness: A review," *Int. J. Comput. Mater. Sci. Surf. Eng.*, vol. 5, no. 1, pp. 68–84, 2012.

- [120] M. Santhanakrishnan, P. S. Sivasakthivel, and R. Sudhakaran, "Modeling of geometrical and machining parameters on temperature rise while machining Al 6351 using response surface methodology and genetic algorithm," *J. Brazilian Soc. Mech. Sci. Eng.* 2015 392, vol. 39, no. 2, pp. 487–496, Jun. 2015.
- [121] P. S. Sivasakthivel and R. Sudhakaran, "Optimization of machining parameters on temperature rise in end milling of Al 6063 using response surface methodology and genetic algorithm," *Int. J. Adv. Manuf. Technol.*, vol. 67, no. 9–12, pp. 2313–2323, Aug. 2013.
- [122] S. Debnath, M. M. Reddy, and Q. S. Yi, "Influence of cutting fluid conditions and cutting parameters on surface roughness and tool wear in turning process using Taguchi method," *Measurement*, vol. 78, pp. 111–119, Jan. 2016.
- [123] V. Vasu and G. P. K. Reddy, "Effect of minimum quantity lubrication with Al 2O₃ nanoparticles on surface roughness, tool wear and temperature dissipation in machining Inconel 600 alloy," *Proc. Inst. Mech. Eng. Part N J. Nanoeng. Nanosyst.*, vol. 225, no. 1, pp. 3–15, Mar. 2012.
- [124] A. C. S, A. M. H, A. C. K, A. P. M, and R. Rajan, "Measurement of Cutting Temperature during Machining," *IOSR J. Mech. Civ. Eng. e-ISSN*, vol. 13, no. 2, pp. 102–116.
- [125] K. A. Risbood, U. S. Dixit, and A. D. Sahasrabudhe, "Prediction of surface roughness and dimensional deviation by measuring cutting forces and vibrations in turning process," *J. Mater. Process. Technol.*, vol. 132, no. 1–3, pp. 203–214, Jan. 2003.
- [126] M. Brezocnik, M. Kovacic, and M. Ficko, "Prediction of surface roughness with genetic programming," *J. Mater. Process. Technol.*, vol. 157–158, no. SPEC. ISS., pp. 28–36, Dec. 2004.
- [127] A. M. Zain, H. Haron, and S. Sharif, "Application of GA to observe the optimal

- effect of the radial rake angle for minimising surface roughness in end milling,” *Int. J. Mach. Mach. Mater.*, vol. 8, no. 3/4, p. 283, 2010.
- [128] H. M. C. M. H. K. C. Wickramasinghe, G. I. P. Perera, “Formulation and Performance Evaluation of a Novel Coconut Oil-based Metalworking Fluid,” pp. 1–27, 2017.
- [129] W. L. R. Fernando, N. Sarmilan, K. C. Wickramasinghe, H. M. C. M. Herath, and G. I. P. Perera, “Materials Today : Proceedings Experimental investigation of Minimum Quantity Lubrication (MQL) of coconut oil based Metal Working Fluid,” *Mater. Today Proc.*, no. xxxx, 2019.
- [130] Alibaba.com, “Nano Comparision.” [Online]. Available: <https://www.alibaba.com/detail/compareProducts.html?ids=1600336932381,1600486328033,1600191865971,1600397702495,1600278768231,62012739070&compareId=890fa549b2be48709597c384214d4944&pids=>. [Accessed: 18-May-2022].
- [131] H. M. Ali, H. Babar, T. R. Shah, M. U. Sajid, M. A. Qasim, and S. Javed, “Preparation Techniques of TiO₂ Nanofluids and Challenges: A Review,” *Appl. Sci. 2018, Vol. 8, Page 587*, vol. 8, no. 4, p. 587, Apr. 2018.
- [132] L. S. Sundar, K. V. Sharma, M. K. Singh, and A. C. M. Sousa, “Hybrid nanofluids preparation, thermal properties, heat transfer and friction factor – A review,” *Renew. Sustain. Energy Rev.*, vol. 68, no. March 2016, pp. 185–198, 2017.
- [133] A. A. Junankar *et al.*, “Materials Today : Proceedings A Review : Enhancement of turning process performance by effective utilization of hybrid nanofluid and MQL,” *Mater. Today Proc.*, no. xxxx, 2020.
- [134] W. Tasnim, M. M. Rahman, K. Kadirgama, D. Ramasamy, and M. A. Maleque, “Materials Today : Proceedings An overview on synthesis , stability , opportunities and challenges of nanofluids,” *Materials Today: Proceedings*, 2021. .

- [135] M. Y. Noordin, V. C. Venkatesh, S. Sharif, S. Elting, and A. Abdullah, "Application of response surface methodology in describing the performance of coated carbide tools when turning AISI 1045 steel," *J. Mater. Process. Technol.*, vol. 145, no. 1, pp. 46–58, Jan. 2004.
- [136] S. A. S. Amiril, E. A. Rahim, and A. Z. Hishamudin, "Effect of nozzle distance and cutting parameters on MQL machining of AISI 1045," *J. Phys. Conf. Ser.*, vol. 1150, no. 1, 2019.
- [137] A. Yassin and C. Y. Teo, "Effect of Pressure and Nozzle Angle of Minimal Quantity Lubrication on Cutting Temperature and Tool Wear in Turning," *Appl. Mech. Mater.*, vol. 695, pp. 676–679, 2014.
- [138] R. Kumar, S. Amit, R. Dixit, A. Mandal, and A. Kumar, "Emerging application of nanoparticle - enriched cutting fluid in metal removal processes : a review," *J. Brazilian Soc. Mech. Sci. Eng.*, 2017.
- [139] B. Rahmati, A. A. D. Sarhan, and M. Sayuti, "Investigating the optimum molybdenum disulfide (MoS₂) nanolubrication parameters in CNC milling of AL6061-T6 alloy," pp. 1143–1155, 2014.
- [140] Y. H. Chai, S. Yusup, V. S. Chok, M. T. Arpin, and S. Irawan, "Investigation of Thermal Conductivity of Multi Walled Carbon Nanotube Dispersed in Hydrogenated Oil Based Drilling Fluids," *Appl. Therm. Eng.*, 2016.
- [141] P. Kalita, A. P. Malshe, and K. P. Rajurkar, "CIRP Annals - Manufacturing Technology Study of tribo-chemical lubricant film formation during application of nanolubricants in minimum quantity lubrication (MQL) grinding," *CIRP Ann. - Manuf. Technol.*, vol. 61, no. 1, pp. 327–330, 2012.
- [142] C. Mao, H. Zou, and X. Huang, "The influence of spraying parameters on grinding performance for nanofluid minimum quantity lubrication," pp. 1791–1799, 2013.
- [143] M. Sayuti, A. A. D. Sarhan, and M. Hamdi, "An investigation of optimum SiO₂

nanolubrication parameters in end milling of aerospace Al6061-T6 alloy,” pp. 833–849, 2013.

- [144] S. Sharif, I. O. Sadiq, and M. A. Suhaimi, “Overview of Nanofluid Application through Minimum Quantity Lubrication (MQL) in Metal Cutting Process,” vol. 20199, 2017.
- [145] A. Mishra, “Application of Taguchi method in optimization of toolflank wear width in turning operation of AISI 1045 steel.”
- [146] A. Qasim, S. Nisar, A. Shah, M. Saeed, and M. A. Sheikh, “Simulation Modelling Practice and Theory Optimization of process parameters for machining of AISI-1045 steel using Taguchi design and ANOVA,” *Stimul. Model. Pract. THEORY*, vol. 59, pp. 36–51, 2015.
- [147] E. Kilickap, M. Huseyinoglu, and A. Yardimeden, “Optimization of drilling parameters on surface roughness in drilling of AISI 1045 using response surface methodology and genetic algorithm,” pp. 79–88, 2011.
- [148] Z. Xiao, X. Liao, Z. Long, and M. Li, “Effect of cutting parameters on surface roughness using orthogonal array in hard turning of AISI 1045 steel with YT5 tool,” *Int. J. Adv. Manuf. Technol.*, 2016.
- [149] A. Bhattacharya, Æ. S. Das, and P. M. Æ. A. Batish, “Estimating the effect of cutting parameters on surface finish and power consumption during high speed machining of AISI 1045 steel using Taguchi design and ANOVA,” pp. 31–40, 2009.
- [150] N. S. T. T. S. Gobikannan, “Application of Response Surface Methodology and Firefly Algorithm for Optimizing Multiple Responses in Turning AISI 1045 Steel,” pp. 8015–8030, 2014.
- [151] METALWORKING SOLUTIONS COMPANY, “Effects of Cutting Conditions for Turning | MITSUBISHI MATERIALS CORPORATION,” *MITSUBISHI*

- MATERIALS*, 2021. [Online]. Available: http://www.mitsubishicarbide.com/en/technical_information/tec_turning_tools/tec_hsk-t/tec_hsk-t_technical/tec_turning_effects. [Accessed: 13-May-2022].
- [152] S. A. Lawal, I. A. Choudhury, and Y. Nukman, "A critical assessment of lubrication techniques in machining processes: A case for minimum quantity lubrication using vegetable oil-based lubricant," *J. Clean. Prod.*, vol. 41, pp. 210–221, 2013.
- [153] S. Ekinović, E. Begović, and A. Lušija, "MQL Machining – Oil on Water Droplet System," *4th Int. Symp. Sustain. Dev.*, no. September, pp. 15–25, 2013.
- [154] A. Çiçek, T. Kivak, and G. Samtas, "Application of taguchi method for surface roughness and roundness error in drilling of AISI 316 stainless steel," *Stroj. Vestnik/Journal Mech. Eng.*, vol. 58, no. 3, pp. 165–174, 2012.
- [155] K. N. Bharath, G. B. Manjunatha, and K. Santhosh, *Failure analysis and the optimal toughness design of sheep-wool reinforced epoxy composites*. Elsevier Ltd, 2018.
- [156] J. Laxman and K. G. Raj, "Mathematical modeling and analysis of EDM process parameters based on Taguchi design of experiments," *J. Phys. Conf. Ser.*, vol. 662, no. 1, 2015.
- [157] M. Nouioua, M. A. Yallese, R. Khettabi, S. Belhadi, M. L. Bouhalais, and F. Girardin, "Investigation of the performance of the MQL, dry, and wet turning by response surface methodology (RSM) and artificial neural network (ANN)," *Int. J. Adv. Manuf. Technol.*, vol. 93, no. 5–8, pp. 2485–2504, 2017.
- [158] A. Rathi, A. Mahor, R. Ranjan, A. Gajbhiye, A. Rehman, and C. M. Krishna, "Prediction of Chip Morphology for Aluminum Metal Matrix Composites in End Milling Machining," *Univers. J. Mech. Eng.*, vol. 2, no. 7, pp. 240–247, 2014.
- [159] M. Sarikaya and A. Güllü, "Multi-response optimization of minimum quantity lubrication parameters using Taguchi-based grey relational analysis in turning of

- difficult-to-cut alloy Haynes 25,” *J. Clean. Prod.*, vol. 91, pp. 347–357, 2015.
- [160] O. Öndin, T. Kivak, M. Sarikaya, and Ç. V. Yıldırım, “Investigation of the influence of MWCNTs mixed nanofluid on the machinability characteristics of PH 13-8 Mo stainless steel,” *Tribol. Int.*, vol. 148, p. 106323, Aug. 2020.
- [161] R. Amdoun *et al.*, “The Desirability Optimization Methodology; a Tool to Predict Two Antagonist Responses in Biotechnological Systems: Case of Biomass Growth and Hyoscyamine Content in Elicited *Datura starmonium* Hairy Roots,” *Iran. J. Biotechnol.*, vol. 16, no. 1, pp. 11–19, Feb. 2018.
- [162] G. Derringer and R. Suich, “Simultaneous Optimization of Several Response Variables,” *J. Qual. Technol.*, vol. 12, no. 4, pp. 214–219, Oct. 1980.
- [163] M. Huo *et al.*, “Understanding the role of water-based nanolubricants in micro flexible rolling of aluminium,” *Tribol. Int.*, vol. 151, p. 106378, Nov. 2020.
- [164] Z. Said *et al.*, “Enhancing the performance of automotive radiators using nanofluids,” *Renew. Sustain. Energy Rev.*, vol. 112, pp. 183–194, Sep. 2019.
- [165] P. A. Jadhav and R. Deivanathan, “Numerical analysis of the effect of air pressure and oil flow rate on droplet size and tool temperature in MQL machining,” *Mater. Today Proc.*, vol. 38, pp. 2499–2505, Jan. 2021.
- [166] T. M. Duc, T. T. Long, and N. M. Tuan, “Performance investigation of mql parameters using nano cutting fluids in hard milling,” *Fluids*, vol. 6, no. 7, 2021.
- [167] H. Saglam, S. Yaldiz, and F. Unsacar, “The effect of tool geometry and cutting speed on main cutting force and tool tip temperature,” *Mater. Des.*, vol. 28, no. 1, pp. 101–111, Jan. 2007.
- [168] N. Lungu and M. Borzan, “EFFECT OF CUTTING SPEED AND FEED RATE ON TOOL GEOMETRY, TEMPERATURE AND CUTTING FORCES IN MACHINING AISI 1045 CARBON STEEL USING FEM SIMULATION,” *Proc. Manuf. Syst.*, vol. 7, no. 4, 2012.

- [169] A. K. Sharma, J. K. Katiyar, S. Bhaumik, and S. Roy, "Influence of alumina / MWCNT hybrid nanoparticle additives on tribological properties of lubricants in turning operations," vol. 7, no. 2, pp. 153–168, 2019.
- [170] A. Thakur, A. Manna, and S. Samir, "Experimental investigation of nanofluids in minimum quantity lubrication during turning of EN-24 steel," *Proc. Inst. Mech. Eng. Part J J. Eng. Tribol.*, vol. 234, no. 5, pp. 712–729, 2020.
- [171] H. Babar and H. M. Ali, "Towards hybrid nanofluids: Preparation, thermophysical properties, applications, and challenges," *J. Mol. Liq.*, vol. 281, pp. 598–633, May 2019.